




Office de la propriété
intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An Agency of
Industry Canada

43



*Bureau canadien
des brevets*
Certification

*Canadian Patent
Office*
Certification

La présente atteste que les documents
ci-joints, dont la liste figure ci-dessous,
sont des copies authentiques des docu-
ments déposés au Bureau des brevets.

This is to certify that the documents
attached hereto and identified below are
true copies of the documents on file in
the Patent Office.

Specification and Drawings, as originally filed with Application for Patent Serial No:
2,327,211, on December 1, 2000, by **NORTEL NETWORKS LIMITED**, assignee of
Donald R. Horne, for "Management of Log Archival and Reporting for Data Network
Security Systems"

RECEIVED
FEB 15 2002
Technology Center 2100

**CERTIFIED COPY OF
PRIORITY DOCUMENT**

Agent certificateur/Certifying Officer

December 19, 2001

Date

Canada

(CIPO 68)
01-12-00

OPIC CIPO

**MANAGEMENT OF LOG ARCHIVAL AND REPORTING FOR
DATA NETWORK SECURITY SYSTEMS**

FIELD OF THE INVENTION

5

This invention relates to management of security systems for data communications networks, and in particular relates to security audit logs and management of security device log archival and reporting.

10

BACKGROUND OF THE INVENTION

With increasing regularity, public and private data networks are interconnecting mission critical systems. As a result, the security of these data networks has become a growing concern. Security audit logs provide a mechanism for detecting compromise of network devices by maintaining an audit trail of user activities and events generated by the various systems that make up the network.

20

Audit trails provide a means to accomplish several security related objectives. These include, for example, individual accountability, reconstruction of past events, intrusion detection and problem analysis.

25

Basic security log reporting is provided by several companies products , e.g. WebTrends™ and Telemate™ which are two of the most popular firewall log analysis products currently on the market.

30

Nevertheless, these applications are currently limited in their ability to scale to large enterprises and global operations. There are currently no offerings available which would be suitable for large carrier class customers
5 (ASPs Application Service Providers and Internet Service Providers ISPs).

These systems are increasingly complex, and link heterogeneous security devices, e.g. firewalls, extranet
10 switches and drop boxes, distributed globally.

The lack of scalability of current systems arises from several factors.

- 15 • Current systems archive logfiles to a general database table where logfile analysis is then done by performing select queries using the fields defined in the database table. This is not a scalable solution today, and will become even less so as the volumes of data increase.
- 20 • One of the main issues in scaling current systems is that they involve a direct connection of all security devices to the main logging/archival server, which is not compatible with globally distributed systems.
- 25 • Security is an issue where, as in current systems, all security devices need to contact the log archival server, and it is therefore necessary to firewall the one-to-many connection with these units.

30 Thus larger customers need a system which overcomes these issues and provides features including automated summary and performance metrics, custom log analysis capabilities, and an ability to key into unusual activity and possible abuse, and trigger alarms. Other desirable features include trend
35 analysis. Different levels of authorized access are

required and special access capabilities for security investigations.

With respect to archival, typically security logs are
5 treated as confidential corporate data, and may require that security logs are archived anywhere from a few months to a number of years.

SUMMARY OF THE INVENTION

10

Thus the present invention seeks to circumvent or overcome the above mentioned problems by providing a novel architecture for security management systems comprising log archival and reporting for data networks, with particular
15 application for larger scale global data networks.

Thus, according to an aspect of the invention, there is provided a security device log and reporting system wherein archival of log files is separated from analysis of
20 logfiles.

Separation of log file analysis and archival provides for improved scalability of the system.

25 According to another aspect of the invention there is provided security device log and reporting system comprising a Log Manager, the Log Manager having a distributed interface for receiving logfiles from a plurality of security devices, and is the interface to a
30 Data Analysis and Archival unit of the system.

Beneficially the Log manager comprises an intermediary caching system for log files received from the plurality of security devices.

Advantageously, the system comprises an Data Analysis and
5 Archival Unit, a Log Collection Unit comprising a Log
Manager, and Data and system Access Unit, wherein Data
Analysis and Archival Unit interfaces with only a Log
Manager and a Data and System Access Unit, whereby
interfaces are easily protected via a firewall and
10 intrusion detection system.

Another aspect of the invention provides a security device
log and reporting system for a data network, comprising:
a Log Collection unit, for collecting log files from
15 security devices,
a Data Analysis and Log Archival unit for analysis and
archival of log files,
and a Data and System Access Unit providing a user interface
with the Data Analysis and Log Archival Unit.

20

Beneficially, the Log Collection unit comprises a Log
Manager for managing log collection from a plurality of
security devices.

25 Alternatively, the Log Collection unit comprises a
plurality of log collectors and a log collection manager for
managing log collection from a plurality of log collectors.

Another aspect of the invention provides a data network
30 security management system for security device log archival
and reporting comprising:

a log collection units comprising a plurality of log collectors, each for collecting log files from a plurality of security device node and a log manager for collecting log files from a plurality of log collectors;

5 a data analysis and log archival unit for archival and automated analysis of log files received from the log manager.

and a data and system access unit providing a user interface to the Data Analysis and Log Archival Unit.

10

The log collector provides output to a storage manager and a Data Analysis manager, connected to a Data Analysis Store, of the Data Analysis and Log Archival unit, which also comprises a Archival unit associated with the Storage unit.

15 Preferably, the user interface is a web based user interface, and the data and system access unit wherein the user interface provides for log analysis summaries, trend analysis, controlled operational access and system configuration

20

For security, the access unit comprises an authenticated, authorized, secured web based system.

The system is designed so that the log collector may receive
25 logfiles from security devices comprising one or more device types including:

Firewalls, (raptor 4, Raptor 6, CES CheckPoint Firewall-1)

Remote access services (RAS),

CES (Contivity Extranet Switch),

30 SPAM (Mail shield),

FTP Drop Box

and Anti-Virus (Antigen)

According to another aspect of the invention, there is provided system wherein the Log Manager LM interfaces with a Data Analysis Manager (DAM) and a Storage Manager (SM) and the LM comprises:

means for collecting logfiles from security devices,
means for pushing cached SD logfiles to a Storage manager for archival, and
means for providing log archival status updates to a Data
Analysis Manager (DAM).

Another aspect of the invention provides a Log Manager for a data network security management system, wherein the Log Manager LM interfaces with a Data Analysis Manager (DAM) and a Storage Manager (SM) and the LM comprises:

means for collecting logfiles from security devices, means for pushing cached SD logfiles to a Storage manager for archival, and means for providing log archival status updates to a Data Analysis Manager (DAM).

In another system according to the invention, the Log Collector Manager (LCM) interfaces with a Data Analysis Manager (DAM) and a Storage Manager (SM) and the LCM comprises:

means for receiving logfiles from the plurality of log collectors,
means for obtaining a logging system configuration from the DAM,
means for propagating the configuration to individual LC associated with Security devices,
means for providing notification to the LC to begin transfer of SD log files, and

means for pushing cached SD log files to the Storage manager for archival, and

means for providing log archival status updates to the DAM.

- 5 According to another aspect of the invention the system includes a Data Analysis and Log Archival unit which comprises a Storage Manager (SM) and a Data Analysis Manager (DAM) and the SM comprises
- means to receive security device logs from the Log Collector Manager,
- 10 means for system archival,
- means for management of online and offline log archival and transition of logs form online to offline status,
- means to provide the Data Analysis Manager (DAM) with access
- 15 to SD logs on request, and
- means to provide the DAM with access to the SM log Archival tables on request.

Beneficially, the system is scalable in a global environment for reasons set out below, and provides for a web interface

20 into the system.

- According to yet another aspect of the invention there is provided a method of managing security device log archival and reporting for a data network security , comprising
- 25 collecting log files from a security device node at a log collector
- collecting log files from a plurality of log collectors at a log collection manager
- transferring log files from the log collection
- 30 manager to a data analysis and log archival unit for archival and analysis.

Yet another aspect of the invention provides a method of managing security device log archival and reporting for a data network security , comprising

5 collecting log files from a security device node at a log collector

 collecting log files from a plurality of log collectors at a log collection manager

 transferring log files from the log collection
10 manager to a data analysis and log archival unit for archival and analysis, logfile analysis being separated from log file archival.

The method may include providing user access to the Data
15 analysis and log archival unit via a data and system access unit.

Another aspect of the invention provides a Storage Manager for a security device log archival and reporting system
20 comprising means for receiving security device logs from the log collector manager for system archival,
means for management of online and offline log archival and transition of logs from online to offline status,
means for providing the DAM with access to security device
25 logs on request,
means for providing the DAM with access to the SM log archival tables on request.

The storage manager beneficially comprises means for
30 differentiating types of log files.

The following factors contribute to scalability that known logging systems do not provide.

- 5 • The separation of logfile analysis from logfile archival. Archival and analysis of logfiles are separated into two separate databases. The archival database (i.e. the Storage Manager), manages where logfiles are physically located on media, as well as the attributes of the logfile. The analysis of the logfile is done
10 independently of a database with only the results of the analysis stored in the analysis database (i.e. the Data Analysis Store). This does not preclude subsequent analyses of a logfile as the logfile is still available. This approach differs from current systems which archive
15 logfiles to a general database table where logfile analysis is then done by performing select queries using the fields defined in the database table.
- 20 • The Log Manager is architected and designed to be the distributed interface for devices to input their logs. The Log Manager then becomes the interface to the archival and analysis servers of the system. The Log Manager also acts as an intermediary caching system
25 allowing end devices to offload their logs in a more efficient manner. As Log Managers can be globally distributed yet still be centrally managed this increases the scalability of the system.
- 30 • The system is architected such that the log archival and analysis components are easily secured via a firewall and intrusion detection system. This is achievable by the distributed components of the system. The only physical machines that need to interface with the archival and
35 analysis components of the system are the Log Managers and the Web Application Server (i.e. machine which hosts the web interface). Instead of having to firewall a one-to-many relationship found in current systems where all devices need to contact the log archival server, one only has to firewall a one-to-few relationship. The effect is
40 that a larger, secure archival system is achievable whereas to achieve the same security with other systems it would mean managing multiple contexts of the system. This is important in that the invention is architected and designed for the analysis and archival of
45 confidential data.

- The ability to differentiate types of logfiles as per legal and corporate security requirements is not currently available in any other system.

5 In a system currently in operation the system handles the archival and analysis of 92 globally dispersed security devices on a daily basis. The device archival and analysis is provided for firewalls (Raptor 4, Raptor6, CES
Checkpoint Firewall-1) extranet switches and Remote access
10 services, SPAM (Mailshield) and FTP Dropboxes and Anti-Virus. Soon to be in production will be the archival and analysis of Intrusion Detection alarms (Internet Security System's network intrusion detection), and personal firewalls (CyberArmor).

15

The system preferably provides authorisation support for views based on device type, database driven filter configurations and analysis store. Metrics report generation for general metrics, monthly metrics and user
20 metrics may be generated.

Advantageously, the system uses a CORBA (Common Object Request Broker Architecture) driven system backend for communication between the system components.

25

Thus the system provides for many aspects of management of log files according to corporate and legal requirements, automated archival and automated or custom analysis, and logfile exception reporting, and for example archival and
30 analysis of ISS vulnerability assessments

Beneficially, such a system can be designed to be multi-vendor interoperable. Operation can be simplified if a standard format for security device logs is adopted.

5

The systems and methods described herein improves the ability of Security Operations to manage an increasingly complex, heterogeneous environment of Security Devices (e.g. firewalls, extranet switches, dropboxes) through support automation, thereby increasing the effectiveness of existing operations personnel. A level of data security is to the infrastructure for the management of security devices protecting corporate resources and the audit capabilities of the security infrastructure are increased. The systems improves the ability to generate security device metrics while providing secure web access to those metrics. The resulting Security Devices Log and Reporting system provides a foundation block for an enterprise security environment called Intrusion Monitoring and Management of Unified Networks Systems (IMMUNESystem).

15
20

Thus, the design of the system is distinguished by its architecture and functionality, in providing a system which is readily scalable for large network applications comprising globally dispersed security devices.

25

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described in greater detail with reference to the attached drawings wherein:

30

Figure 1 shows a schematic representation the IMMUNE security environment comprising a security devices log and reporting system according to an embodiment of the invention;

- 5 Figure 2 shows a logical view of a system according to a second embodiment of the invention ;

Figures 3 to 14 (taken from the design spec document) respectively show examples of screen prints of screen views presented by the Web interface of the Web Application Server, which provides an overview of categories of screen view that may be presented to an authenticated user.

DETAILED DESCRIPTION OF THE EMBODIMENTS

- 15 [note: a glossary of acronyms presented at end of this section, preceding the Claims section]

The IMMUNE security environment according to an embodiment of the invention is represented schematically in Figure 1.

20 The system 10 for security devices log and reporting comprises the Log Collector (LC) 12, Log Manager (LM) 14, and Data Analysis and Log Archival Unit 16, and Data and System Access Unit 18. Log Collector (LC) 12 interfaces to a security device (SD) 20 which node logs events as they are processed, e.g. Firewall transactions. The Log Collector (LC) 12 transfers the security device log to be archived and analysed in IMMUNE to the Log Manager (LM) 14. The Log Manager (LM) 14 may collect logs from multiple log collectors (not shown) for archival and analysis, and then

30 transfers the logfiles to the Data Analysis and Log Archival Unit 16, which performs archival and automated analysis of

the log files. The Data and System Access Unit 18 provides a authenticated, authorised, secured, web based access to the IMMUNE system, and provides log analysis summaries, trend analysis, controlled operations access and system
5 configuration.

The Security Devices Log and Reporting System (SDLRS) according to a second embodiment shown in Figure 2 described below is targeted at improving the management and access to
10 the logging of a plurality heterogeneous Security Devices (SD). for: operational and business value metrics; keying into possible abuse; legal obligations; security investigations. The SDLRS will manage logs on a configurable basis, but the focus is on performing log analysis and log
15 archival for SD on a daily or other regular basis.

The system according to the embodiment shown in Figure 2 was designed to use a known UNIX based system, for example Solaris or HP-UX for the underlying system components such
20 that the hardening of the Operating Systems adds to the overall level of system security.

Available third-party components capable of providing the intended function were used during the design phase when
25 ever possible. The use of Internet standards-based security are utilized whenever possible.

Component Layout and Unit Description

The logical view of the components making up the SDLRS 100
30 is contained in **Figure 2**, which represents the system schematically, with no assumption made as to the ratio of components to computers. The server objects (e.g. Storage

Manager, Log Manager) can run on the same computer or on different computers, which adds to the scalability of the solution.

- 5 There are three distinct parts of the SDLRS 100. These three parts indicated in dotted outline in Figure 2 are:

Log Collection Unit 100

Data Analysis and Log Archival Unit 200

Data and System Access Unit 300

10

The Log Collection Unit 100 comprises the Log Collectors 102 , which are those system modules that operate in conjunction with the logging mechanism provided by Security Devices SD which an enterprise uses to manage data security within the enterprise network. The Log Collectors LC 102 interface directly with a Security device logging mechanism. The Log Collector Manager LCM 104, which provides for co-ordinating the collection of SD logs from a plurality of Log Collectors 102. The LCM 104 transfers the logs to the Log Archival Unit 200 which comprises the "Storage Manager" 202 and the LCM provides also for notifying the "Data Analysis Manager 206" of a list of newly archived SD logs.

- 25 Advantageously, the Log Collector Manager LCM acts as a SD log caching server, and the existence of the Log Collector Manager also allows for the ease of operationally securing the Data Analysis and Log Archival Unit 200 from unnecessary access by other nodes on the network.

30

The Data Analysis and Log Archival Unit comprises the Storage Manager 202 and Data Analysis Manager 206 . Storage

Manager 202 which is responsible for giving the Data Analysis Manager 206 the identification and location of newly arrived logs, and for managing the archival of logs online and offline by Archival unit 204. Also part of the Data Analysis and Log Archival Unit is the Data Analysis Manager 206 and Data Analysis Store 208. Data Analysis Manager 206 provides each system component with configuration details, analyses logs using the appropriate data filter, and sends the extracted metrics to the Data Analysis Store 208. The Data Analysis Store 208 is for storing system configurations, summary and operational metrics, data filter configurations, and job statuses of data analyses.

The Data and System Access Unit 300 comprises the Web Application Server 302, Web server 304 and Web client 306. The Web Application Server 302 includes the applications that allow the user to interface with the SDLRS for functions such as authentication/access, data filters, and system setting configurations, and for the retrieval of summary metrics from the Data Analysis Store 208. As well, the Web Application Server consists of applications which allow the user to interface directly with the Data Analysis Manager 206 for applications such as custom metrics analysis, and raw data log manipulation. The Web Server 304 is responsible for providing the SDLRS screen views to the Web Client 306 for presentation.

In a system currently in operation the system handles the archival and analysis of 92 globally dispersed security devices on a daily basis. The device archival and analysis

is provided for firewalls (Raptor 4, Raptor6, CES
Checkpoint Firewall-1) extranet switches and Remote access
services, SPAM (Mailshield) and FTP Dropboxes and Anti-
Virus. Soon to be in production will be the archival and
5 analysis of Intrusion Detection alarms (Internet Security
System's network intrusion detection), and personal
firewalls (CyberArmor).

10 **Component Detailed Description**

Log Collection Unit:

Log Collector (LC)

A LC may be identified for each SD, or a group of SDs
15 depending on the SD technology. In either case, the LC is
responsible for the following during the log retrieval
process: accessing the SD log(s), securely (i.e.,
authentication, privacy) transferring the SD log(s) to the
Log Collection Manager (LCM); cleanup of transferred log(s)
20 on the SD. As SD logging occurs as a function of the SD
software, the LC will be "tuned" to work for each type of
SD. For example, retrieval of SD log(s) will be on a 24
hour basis by default, but the LC will accept input from the
LCM to increase the frequency of log retrieval in hourly
25 intervals. Cleanup of SD logs will be, typically, on a 7
day basis by default, but the LC will accept input from the
LCM to increase the frequency of log cleanup in daily
intervals.

30 Log Collector Manager (LCM)

The number of LCMs in the system may be one or more with the responsibility of an LCM being that of co-ordination and retrieval of a number of different SD operational and system performance logs. The LCM contacts the Data Analysis Manager (DAM) on a, e.g., 24 hour basis to acquire its assigned SD identification list, and the log retrieval and cleanup configuration settings for the system. During the log retrieval process, the LCM performs the following: initiates the

connection to the LC; provides system configuration updates for log retrieval and log cleanup frequencies to the LC; securely pulls the SD log(s). Logs that have been securely pulled, are then securely pushed to the Storage Manager (SM) for archival with the LCM providing for each log transfer the device type, date, and SD name to the SM. Upon the transfer of an SD log(s) to the SM, the DAM is notified of the job status, and in the case of errors the error code. Upon completion of all log transfers, the LCM notifies the DAM with an "end of transactions" notification.

20

Data Analysis and Log Archival Unit:**Storage Manager (SM)**

The SM is responsible for SD log archival in the correct location, maintaining an index of log archival according to SD and export control configuration settings, and backups of the log archiving system. As part of the log transfer process, the LCM begins a secure log transfer to the SM with the date, device type, and SD name for the log being transferred. From this information, the SM then selects the appropriate on-line archival directory where the log will be written. Upon successful completion of the log transfer, the SM then updates its index of log archival.

30

To manage the transition of logs from on-line to off-line archival, the SM receives from the DAM the log retention configurations for the system on a daily basis. In an operational system, for example, by default the log archival configurations are set at the following: perimeter devices - 3 months on-line and 15 months off-line; export controlled devices - 3 months on-line and 57 months off-line (where a total of 60 month, or 5 year, archival is required); drop-box devices - 3 months on-line and 15 months off-line; devices classified as "other" (e.g. SPAM logs) - 3 months on-line. Other default values may be set as appropriate. The SM then manages the transition of on-line log archival to off-line archival by performing disk cycling, off-line archival backups, and the updating of the log archival index.

Upon receiving log location requests from the DAM, the SM references the archival index for the location of the log. If the log is on-line, then the file path is given to the DAM. If the log is found to be off-line, then the DAM is informed that the log is off-line. Archival information for specific SD logs or for the complete on-line or off-line indices can be provided to the DAM on request.

25

Data Analysis Manager (DAM)

The DAM is responsible for providing the configuration details to the other system components, ensuring that all SD logs are archived, performing data analysis on SD logs, providing summary statistics to the Data Analysis Store (DAS), and querying the SM for log archival information upon request. To perform log

analysis, the DAM runs in two concurrent capable modes:
automated analysis; custom analysis.

In the automated analysis mode, the DAM dynamically
5 determines via DNS lookups the list of SDs from which logs
are to be retrieved. SDs having been assigned
hostnames/aliases that indicate their security function and
geographical location are then categorized into SD lists
associated with the LCM(s) in the system. The system
10 configuration data for log retrieval interval, log cleanup
interval, log storage interval, and filter configurations
are retrieved from the DAS.

When an LCM contacts the DAM, the LCM is provided with the
log retrieval, and log cleanup configurations, as well as
15 the SD list for which that LCM is responsible. The SM is
notified of the system log archival configuration. The DAM
then retrieves the filter configurations for each of the SD
categories. As the LCM(s) notify the DAM of the successful
transfer of SD logs, the DAM then contacts the SM for the
20 location of the SD log such that the appropriate data
filter can be applied to the log. Once the data analysis is
complete, the summary metrics for the SD are saved to the
DAS. The DAM is responsible for managing the list of SD log
retrievals, and the recording of errors and job statuses to
25 the DAS.

In the custom analysis mode, the Web Application Server
(WAS) contacts the DAM and requests log archival
information, or the WAS provides the date, time, SD
30 category, and name for those logs which data analysis is
requested. The DAM contacts the SM for log archival
information, or for the location of the log(s). In the

scenario where a specific log(s) are requested and found to be on-line, then the appropriate data filter configuration is retrieved from the DAS, and presented to the WAS for acceptance. The WAS then
5 provides the DAM with the desired data filter configuration which the DAM then applies to the SD log(s). Summary metrics from the custom data analysis of the log(s) are then provided to the WAS.

10 Data Analysis Store (DAS)

The DAS is a database to which configurations, data metrics, job statuses, and authentication and access levels are stored. Configuration data exists for system archival, log retrieval, log cleanup, and the various SD
15 category data filters. Data metrics derived out of the automated analyses are stored for each SD. Job statuses and errors for all SDs are stored for each period (default is on a per day basis) of data analysis. Access and profile information for viewing system logs and configurations are
20 stored as well.

Data and System Access Unit:

Web Application Server (WAS)

The WAS consists of all the applications which provide the
25 system and data interfaces to the user. The system views consist of the following: system configuration parameters; SD category filter configurations; access and view profile settings for definable user categories; SD and SD category data metrics
30 views and reports; SD raw log view; alarms and job statuses.

The system configuration application presents a view for defining the system parameters: log retrieval frequency; log cleanup frequency; log archival periods; access list of certificates/ids allowed access to the system; profiles
5 which determine what views a user has access to when authenticated. The profiles are configurable for a variable number of SD categories, but by default the profiles are: SECOPS (Security Operations) - access to all functionality; SPAM (i.e. "junk e-mail") - access to SPAM log data; RAS -
10 access to Contivity Extranet switches maintained by RAS; SECINV (Security investigations) - access to specifiable SD logs for security investigations.

The SD data filter application presents a view from which
15 each SD category regular expressions can be defined for automated data analyses and storage.

The SD data metrics applications can be either for general case metrics or custom requested metrics. In both cases, a
20 view for each SD category is presented from which the user can select the data query settings to be retrieved. The application then presents the user with the data either retrieved from the DAS (general case metrics) or from the DAM (custom requested metrics).

25 The alarms and statuses application presents a view which is updated with the error status and job statuses of the retrieval of SD logs. The view is dynamic in that job statuses and errors are retrieved from the DAS on an hourly
30 basis. Errors are highlighted until they have been acknowledged by an administrator. Errors and job statuses for previous dates are retrievable from the DAS.

Web Server (WS)

The WS is the user's access point into the SDLRS via the WAS. The WS authenticates the user, and sets up the SSL
 5 connection between the WS and the user's web interface.

Web Client (WC)

The WC is a web browser capable of interfacing with the WS,
 and hence the SDLRS.

10

Components Inputs and Outputs

This section provides further details of the component
 inputs and outputs used in the system according to the
 embodiment.

15

Log Collector (LC)

Input from LCM:

System_configuration

Retrieval_Interval={default=24 hrs | hourly
 20 interval=1 - 24 hrs}

Cleanup_Interval={ default=7 days | weekly
 interval=1 - 7days)

Output to LCM:

25 Log transfer list

LC_Name {FQHN, IP address}

SD_Name {FQHN, IP address}

Date

Retrieval_Interval

30 Time

Files={file1, file2, file3...}

Errors

23

file 1
file 2
file 3

5 Log Collector Manager (LCM)

Input from DAM:

```

    System_configuration
        Retrieval_Interval={default=24 hrs | hourly
interval=1 - 24 hrs}
10      Cleanup_Interval={ default=7 days | weekly
interval=1 - 7days)
        LC_List={LC_Name1, LC_Name2, LC_Name3...}
        LC_Name 'n'={FQHN, IP address}
        SD_List={SD_Name1, SD_Name 2, SD_Name 3...}
15      SD_Name 'n'={FQHN, IP address}
        LCM_status_request /* request status update of LC log
archiving managed by LCM */

```

Input from LC:

```

20      Log transfer list
        LC_Name {FQHN, IP address}
        SD_Name {FQHN, IP address}
        Date
        Retrieval_Interval
25      Time
        Files={file1, file2, file3...}
        Errors
        file 1
        file 2
30      file 3

```

Output to SM:

23

24

```

Log transfer list
    LCM_Name {FQHN, IP address}
    LC_Name {FQHN, IP address}
    SD_Name {FQHN, IP address}
5    Date
    Retrieval_Interval
    Time
    Files={file1, file2, file3...}
    file 1
10    file 2
    file 3

Output to DAM:
    Log archival transaction complete
15    LCM_Name {FQHN, IP address}
    LC_Name {FQHN, IP address}
    SD_Name {FQHN, IP address}
    Errors
    LCM_archival_complete /*when all logs have been
20 transferred to the SM for that interval*/
    LCM_status_update
        LC_List={LC_Name1, LC_Name2, LC_Name3...}
        LC_Name'n'={FQHN, IP address,
status=[archived | cached |waiting]}
25

Storage Manager (SM)
Input from LCM:
    Log transfer list
        LCM_Name {FQHN, IP address}
30        LC_Name {FQHN, IP address}
        SD_Name {FQHN, IP address}
        Date

```

24

25

```

        Retrieval_Interval
        Time
        Files={file1, file2, file3...}
file 1
5   file 2
    file 3

Input from DAM:
    System_configuration
10   Archival_Duration={type1, type2, type3...}
        type'n'={online=[number_months],
offline=[number_months]}
    Log_Location_Request
        SD_Type
15   SD_Name {FQHN}
        Date
        ONLINE-OFFLINE_bit /* bit 'on' when auto analysis
is being done on newly arrived logs */
        Filepath_List={filepath1, filepath2, filepath3...}
20 /* file path given for restored offline logs */
    Log_Info_Request
        SD_Type
        SD_Name {FQHN}
        Date
25   Online_Table_Request
        Offline_Table_Request

Output to DAM:
    Log_Location_Reply
30   SD_Type /* type derived from name */
        SD_Name {FQHN, IP address}
        Date

```

25

26

```

    Retrieval_Interval
    Time
    File_Location_List={filepath1, filepath2,
filepath3...}
5      filepath'n'={ONLINE_bit, ONLINE=filepath}
    Log_Info_Reply
        SD_Type
        SD_Name {FQHN, IP address}
        LCM_Name
10      LC_Name
        Online_Offline
        Offline_Date
        Online_Date
        Log_Date
15      Retrieval_Interval
        Online_Table_Reply
        Offline_Table_Reply

Online Log Archival Table
20      SD_Type
        SD_Name
        IP_address
        LCM_Name
        LC_Name
25      Archival_Date
        Log_Date
        Retrieval_Interval
        Time={time1, time2, time3...}
        Filepath={filepath1, filepath2, filepath3...}
30
Offline Log Archival Table
    SD_Type

```

26

27

```

SD_Name
IP_address
LCM_Name
LC_Name
5  Offline_Date
   Log_Date
   Retrieval_Interval
   Time={time 1, time2, time3}
   Filepath={N/A, N/A, N/A}

```

10

Data Analysis Manager (DAM)

Input from LCM:

```

   Log archival transaction complete
15   LCM_Name {FQHN, IP address}
      LC_Name {FQHN, IP address}
      SD_Name {FQHN, IP address}
      Errors

   LCM_archival_complete /*when all logs have been
20 transferred to the SM for that interval*/
   LCM_status_update
      LC_List={LC_Name1, LC_Name2, LC_Name3...}
      LC_Name'n'={FQHN, IP address,
status=[archived | cached | waiting]}

```

25

Input from WAS:

```

   Log_Location_Request /* for custom analysis */
      SD_Type
      SD_Name {FQHN, IP address}
30   Date_Range={Date | From_To}
      Online={ONLINE | OFFLINE}

```

27

28

```

        Offline_File_Location_List={filepath1, filepath2,
filepath3...}/* restored filepath known */
        FULL_TEXT={ON | OFF}
        Custom_Metrics_Request
5         Filter_Type={customized filter keys}
        SD_Type
        SD_Name {FQHN}
        Date_Range={Date | From_To}
        Online_Table_Request
10        Offline_Table_Request

Input from SM:
        Log_Location_Reply
        SD_Type
15        SD_Name {FQHN, IP address}
        Date
        Retrieval_Interval
        Time
        File_Location_List={filepath1, filepath2,
20        filepath3...}
                filepath'n'={ONLINE_bit, ONLINE=filepath}
        Log_Info_Reply
        SD_Type
        SD_Name {FQHN, IP address}
25        LCM_Name
        LC_Name
        Online_Offline
        Offline_Date
        Online_Date
30        Log_Date
        Retrieval_Interval
        Online_Table_Reply

```

28

Offline_Table_Reply

Input from DAS:

System_Configuration

```

5      Archival_Duration={type1, type2, type3...}
        type'n'={online=[number_months],
offline=[number_months]}
        Retrieval_Interval={default=24 hrs | hourly
interval=1 - 24 hrs}
10     Cleanup_Interval={ default=7 days | weekly
interval=1 - 7days)
        SDtypes={type1, type2, type3...}
        type'n'={code, description}
        Devicelist={device1, device2, device3...}
15     Filters={filtertype1, filtertype2, filtertype3...}
        filtertype'n'={key1, key2, key3...}
        Alarms={alarmtype1, alarmtype2, alarmtype3...}
        alarmtype'n'={key1, key2, key3...}
        LCMlist={lcm1, lcm2, lcm3...}
20     lcm'n'={FQHN, IPaddr, responsibility}

```

Output to LCM:

SD system configuration file:

```

25     Retrieval_Interval={default=24 hrs | hourly
interval=1 - 24 hrs}
        Cleanup_Interval={ default=7 days | weekly
interval=1 - 7days)
        LC_List={LC_Name1, LC_Name2, LC_Name3...}
        LC_Name 'n'={FQHN, IP address}
30     SD_List={SD_Name1, SD_Name 2, SD_Name 3...}
        SD_Name 'n'={FQHN, IP address}

```

30

LCM_status_request /* request status of LC log
archiving managed by LCM */

Output to SM:

```

5      System_Configuration
        Archival_Duration={type1, type2, type3...}
        type'n'={online=[number_months],
offline=[number_months]}
        Log_Location_Request
10      SD_Type
        SD_Name {FQHN}
        Date
        ONLINE-OFFLINE_bit /* bit 'on' when auto analysis
is being done on newly arrived logs */
15      Filepath_List={filepath1, filepath2, filepath3...}
        Log_Info_Request
        SD_Type
        SD_Name {FQHN}
        Date
20      Online_Table_Request
        Offline_Table_Request

```

Output to WAS:

```

        Full_Text_Reply
25      Logfile_Text_Buffer /* for read-only access */
        Custom_Metrics_Reply
        Metrics_Table
        Status
        Errors
30      Alarms
        Search_Results

```

30

```

Online_Table_Reply /* summary of logs archived online
*/
Offline_Table_Reply /* summary of logs archived offline
*/
5
Output to DAS:
    Session_Analysis
        Date={Month, Day, Year}
        Start_Time
10        Session_ID
        Device_Type
        Logfile_Type
        Logfile_Date_Time
        Retrieval_Interval
15    Session_Results
        Date={Month, Day, Year}
        Completion_Time
        Session_ID
        Device_Type
20        Logfile_Type
        Logfile_Date_Time
        Error_Code
        Alarms={none | [alarm1, alarm2, alarm3...]}
        Errors={none | [error1, error2, error3...]}
25        Metrics={key1results, key2results, key3results...}
            key'n'results={hit1, hit2, hit3...}
    Device_Update
        Device_Type
        Device_Name
30        Status={ACTIVE, HISTORIC}

```

Data Analysis Store (DAS)

Database Schema

TABLE: analysis_session (used to store information about the logfile analysis)

5 FIELDS:

```

        session_id /* incorporate the date into the
sessionid */
        year /* Required for */
        month /* ease of extraction of */
10      day /* summary metrics.*/
        device_type (name of firewall contivity switch,
spam machine,...)
        logfile_type (type of file that was parsed. ie.
some SDs will produce a number of logfiles)
15      logfile_date (date and time of logfile)
        retrieval_interval (system log retrieval rate)
        start_time /* required to track DAM-system */
        completion_time /* performance */

```

TABLE: session_alarms

20

FIELDS:

```

        session_id
        alarmcode
        status /* status of each alarm - active or
25 acknowledged */
        severity

```

TABLE: session_errors

30

FIELDS:

```

        session_id
        errorcode

```

status /* status of each error - active or
acknowledged */

severity

TABLE: logfile_types (used to store information about
5 versions of software e.g., firewall - Raptor 4.0 vs Raptor
6.0)

FIELDS:

device_type
10 logfile_type

TABLE: metric_types (used to store information about the
metrics that need to be calculated and where to find the
results)

15

FIELDS:

metric_id (this will be a number from 1 - 30 and
is the place where the results are stored in the tables. For
example, if this has a value of 2, then in the individual
20 results tables the result of this metric is stored in the
metric2 field.)

device_type (ie.
FIREWALL, SPAM, CONTIVITY, FTPDROPBOX, USER_STATS)

logfile_type (e.g. Raptor 4, Raptor 6)
25 metric_name (this is the name that is used to
describe the particular metric being found ie. Number of FTP
connects)

metric_key (this is the value that is being
searched ie. ftp.*connection for)

30 status (as we are storing all metrics for many
years in the database, a particular metric that was used in
the past may no longer be valid but still requires a

placeholder in the database for historic data. The possible entries in this field are ACTIVE, or HISTORIC where if the status is ACTIVE, then it will be used for analysis)

TABLE: user_table (used to store information about the users
5 accessing this tool)

FIELDS:

userid (ie. CN for certs or userid)
device_type (i.e.
10 ALL, FIREWALL, SPAM, CONTIVITY, FTPDROPBOX, USER_STATS)
type_of_access (e.g. DBA, ANALYST, HELPDESK, CORP-
INVESTIGATIONS)
user_name
user_phone
15 TABLE: access (used to store information about the different
levels of access)

FIELDS:

type_of_access (e.g. DBA, ANALYST, HELPDESK, CORP-
20 INVESTIGATIONS)
TABLE: special_access (used to determine access rights to a
log in scenarios where specific, limited access is granted)

FIELDS:

25 userid (ie. CN for certs or userid)
device_name (i.e. ALL, FQHN(S)) /* required for
security investigations */
date (i.e. ALL, DATE RANGE) /* required for
security investigations */
30 TABLE: firewall (used to store the metrics gathered on a per
firewall basis per logfile basid - for the first cut there
will be one entry per firewall per day but as the

processing becomes more often, there may be many per
firewall per day.)

FIELDS:

5 session_id
 metric1 to metric 30 (used for counts and sums)
TABLE: firewall_monthly (used to store firewall information
but summarized by month)

10 FIELDS:

 firewall
 year
 month
 metric1 to metric 30
15 TABLE: firewall_user (used to store firewall information
based on the USER_STATS)

FIELDS:

 transaction_type - things like connects per
20 userid, bytes transferred per userid, etc. This information
is done on a per firewall per logfile basis)
 session_id
 userid
 metric1 to metric 30
25 TABLE: firewall_keyword (used to store the matched keyword
information. This is done on a per firewall per logfile
basis.)

FIELDS:

30 session_id
 search_key
 matched_line (string where the match was found)

userid (if possible, the userid extracted from the matched line)

count(?) (ongoing count rather than additional entries in the db?)

5 TABLE: contivity (used to store the metrics gathered on a per contivity basis per logfile basis)

FIELDS:

session_id
10 metric1 to metric 30 (counts and sums)
TABLE: contivity_monthly (used to store contivity information but summarized by month)

FIELDS:

15 contivity
year
month
metric1 to metric 30
TABLE: contivity_user (used to store contivity information
20 based on the USER_STATS)

FIELDS:

transaction_type (things like connects per userid, bytes transferred per userid, etc. this information is done
25 on a per contivity per logfile basis)
session_id
userid
metric1 to metric 30
TABLE: contivity_keyword (used to store the matched keyword
30 information. This is done on a per contivity per logfile basis.)

FIELDS:

session_id
 search_key
 matched_line (string where the match was found)
 5 .userid (if possible, the userid extracted from the
 matched line)
 count(?) (ongoing count rather than additional
 entries in the db?)
 TABLE: dropbox (used to store the metrics gathered on a per
 10 dropbox basis per logfile basis)

FIELDS:

session_id
 metric1 to metric 30
 15 TABLE: dropbox_monthly (used to store dropbox information
 but summarized by month)

FIELDS:

dropbox
 20 year
 month
 metric1 to metric 30
 TABLE: dropbox_user (used to store firewall information
 based on the USER_STATS)

25

FIELDS:

 transaction_type - things like connects per
 userid, bytes transferred per userid, etc. this information
 is done on a per dropbox per logfile basis)
 30 session_id
 userid
 metric1 to metric 30

TABLE: dropbox_keyword (used to store the matched keyword information. This is done on a per firewall per logfile basis.)

5 FIELDS:

 session_id
 keyword_key (key that was looked for)
 matched_line (string where the match was found)
 userid (if possible, the userid extracted from the
10 matched line)
 count(?) (ongoing count rather than additional
entries in the db?)

TABLE: list_contivity (used to store the list of contivities that have information stored in this database)

15

 FIELDS:

 device_status (as we are storing metrics for many
contivities for many years in the database, a particular
contivity that was used in the past may no
20 longer be valid but still requires a placeholder
in the database for historic data. The possible entries in
this field are ACTIVE, or HISTORIC where if the
 status is ACTIVE, then it will be used for
analysis)
25 device_name
 logfile_type

TABLE: list_dropboxes (used to store the list of dropboxes that have information stored in this database)

30 FIELDS:

device_status (as we are storing metrics for many dropboxes for many years in the database, a particular dropbox that was used in the past may no

longer be valid but still requires a placeholder
 5 in the database for historic data. The possible entries in this field are ACTIVE, or HISTORIC where if the status is ACTIVE, then it will be used for analysis)

device_name

10 logfile_type

TABLE: list_firewalls (used to store the list of firewalls that have information stored in this database)

FIELDS:

15 device_status (as we are storing metrics for many firewalls for many years in the database, a particular firewall that was used in the past may no longer be valid but still requires a placeholder in the database for historic data. The possible entries in this
 20 field are ACTIVE, or HISTORIC where if the status is ACTIVE, then it will be used for analysis)

device_name

logfile_type

TABLE: list_keywords (used to store the list of keywords
 25 that are to be used as part of an analysis)

FIELDS:

search_key (search string)

device_type

30 logfile_type

40

responsibility (group who supplied the keyword and
 is responsible to investigate when found - HR (Human
 Resources), NS (Network Security), CS
 (Corporate Security))

5 status (as we are storing metrics for many
 firewalls for many years in the database, a particular
 firewall that was used in the past may no longer be valid
 but still requires a placeholder in the database
 for historic data. The possible entries in this field are
 10 ACTIVE, or HISTORIC where if the status is
 ACTIVE, then it will be used for analysis)
 TABLE: mailshield (used to store mailshield metrics)

FIELDS:

15 session_id
 metric1 to metric 30 (sum and counts)
 logfile_type
 TABLE: spam_rejections (used to store top 10 rejection
 types)

20

FIELDS:

session_id
 reject1 to reject10
 occurrence1 to occurrence10
 25 TABLE: list_mailshields (used to store the list of
 mailshields that have information stored in this database)

FIELDS:

device_status (as we are storing metrics for many
 30 mailshields for many years in the database, a particular
 mailshield that was used in the past may no

longer be valid but still requires a placeholder
in the database for historic data. The possible entries in
this field are ACTIVE, or HISTORIC where if the
status is ACTIVE, then it will be used for

5 analysis)

device_name

TABLE: mailshield_monthly (used to store mailshield
information but summarized by month)

10 FIELDS:

mailshield

year

month

metric1 to metric 30

15 TABLE: blocked (used to store blocked metrics)

FIELDS:

session_id

recipient_emailid

20 reason (store the reason that the email was
blocked)

subject (the subject of the blocked email)

sender

TABLE: owners

25

FIELDS:

responsibility (ie, HR (Human Resources, NS
(Network Security), CS (Corporate Security))

contact_name (person to contact when matched)

30 userid

contact_phone

contact_email (This is key so that an email can be sent out, assuming we decide to automate this function)

TABLE: error_list (used to store information about possible system errors)

5

FIELDS:

errorno

severity

description

10 TABLE: alarm_list (used to store information about log alarms)

FIELDS:

alarmcode

15 severity

description

TABLE: device_types (used to store list of valid device_types - these will be hard-coded into this table)

20 FIELDS:

device_type (i.e. FIREWALL, CONTIVITY, SPAM,...)

TABLE: lcm_list (used to store list of Log Collector Managers)

25 FIELDS:

device_name

responsibility (string - depending on implementation could be geographic or device type dependent)

TABLE: sys_config (used to store list of system parameters)

30

FIELDS:

retrieval_interval

43

```
cleanup_interval
device_type
online_duration
offline_duration
```

5

Web Application Server (WAS)**WAS SCREENS:**

The WAS provides a graphical user interface and Figures 2 to
10 13 show some typical screen views which may be selected and
which are intended to give a summary of the categories of
screen views that would be presented to an authenticated
user. This summary is not a complete representation of all
SDLRS screen views and is shown by way of example.

15

The screen views which a user may select are based upon the
user authenticating themselves to the SDLRS, and the access
rights that the SDLRS grants to the user upon that
authentication. Depending on the authenticated user's access
20 rights, the appropriate functionality tabs at the top of
each screen view will be displayed for selection.

Figure 2 represents a Splash Screen with Authentication:
After login and authentication by e.g. an authenticated
25 Security Operations user, the user is presented with the
main menu as shown in Figure 3, providing options tabs
(depending on user access rights) to select Metric Results,
Configure Filters, Job status , Logs Archived and Admin
functions. Selection of the metric results screen as shown
30 in Figure 4 provides options to select results for e.g.
firewalls, connectivity switches, FTP drop boxes, SPAM,
Corporate security, or return to the main menu.

43

The screen shown in Figure 5 represents a security devices metrics menu for firewalls. and the subsequent screen in Figure 6 shows the daily metrics screen for firewalls example.

A daily keywords results screen is shown in Figure 7 and monthly metrics screen in Figure 8.

10 User statistics metrics screen, configure filter screen, and systems job status screen are shown in Figures 9, 10 and 11 respectively. The system logs archived screen, and system administration screen are shown in Figure 12 and 13 respectively.

15

WAS DATA:

Input from WS:

Authentication_Request /* for logging purposes */

Userid

20 IP Address

Interactions with the DAS (Input/Output):

System_Configuration

Archival_Duration={type1, type2, type3...}

25 type'n'={online=[number_months],

offline=[number_months]}

Retrieval_Interval={default=24 hrs | hourly
interval=1 - 24 hrs}

Cleanup_Interval={ default=7 days | weekly
30 interval=1 - 7days)

SDtypes={type1, type2, type3...}

type'n'={code, description}

45

```

    Devicelist={device1, device2, device3...} /*
Informational only as configured dynamically by the DAM */
    Filters={filtertype1, filtertype2, filtertype3...}
        filtertype'n'={key1, key2, key3...}
5    Alarms={alarmtype1, alarmtype2, alarmtype3...}
        alarmtype'n'={key1, key2, key3...}
    LCMlist={lcm1, lcm2, lcm3...}
        lcm'n'={FQHN, IPAddr, responsibility}
    Auth_Access_List
10    CN_List={user1, user2, user3...}
        user'n'={access_level}
        Access_List={access_level1, access_level2,
access_level3...}
    Session_Status
15    Date
        Sessions={session1, session2, session3...}
            session'n'={status, error[1,2,3...],
alarm[1,2,3...]}
                error'n'={errorcode, description}
20    alarm'n'={description}
    Metrics_Reply
        Device_Name
        Metric1 to Metric30

25    Input from DAM:
        Full_Text_Reply
            Logfile_Text_Buffer /* for read-only access */
        Custom_Metrics_Reply
            Metrics_Table
30    Status
        Errors
        Alarms

```

45

46

Search_Results

```

Online_Table_Reply /* summary of logs archived online
*/
Offline_Table_Reply /* summary of logs archived offline
5 */

```

Output to DAM:

```

Log_Location_Request /* for custom analysis */
    SD_Type
10    SD_Name {FQHN, IP address}
    Date_Range={Date | From_To}
    Online={ONLINE | OFFLINE}
    Offline_File_Location_List={filepath1, filepath2,
filepath3...}/* restored filepath known */
15    FULL_TEXT={ON | OFF}
    Custom_Metrics_Request
    Filter_Type={customized filter keys}
    SD_Type
    SD_Name {FQHN}
20    Date_Range={Date | From_To}
    Online_Table_Request
    Offline_Table_Request

```

Output to WS:

```

25    Data fills for presentation

```

Web Server (WS)

```

    Authenticates and establishes secure connection
    Presentation of system to end user

```

Detailed design information for embodiment comprising a Log Manager (LM)

In the embodiment described above, the Log collection unit comprises distinct Log Collector Manager (LCM) and Log Collector (LC) components, which are described in further detail in the LCM Design section and LC Design section following .

In the embodiment shown schematically in Figure 1, the the log collection unit comprises a Log Manager (LM), this component of the Security Devices Log Reporting System (SDLRS), which is responsible for the collecting of Security Device (SD) operational logs, and the transferring of those logs to the Storage Manager (SM) for archival. In fulfilling this role, the LM also has a corresponding interaction with the Data Analysis Manager (DAM) component of the SDLRS.

The intent of this section is to provide the architecture and design of the LM and not the implementation specifics of the LM. For the ease of understanding the LM system, configuration files and tables detailed in the design, as well as example content and records are provided to highlight key fields and information that are required by the LM. The actual implementation of the files and table content may vary.

The log manager functions to

- 1 provide a collection point for Security Devices (SD) to transfer their logfiles for archival.

- 2 Push the cached SD logfiles to the Storage Manager (SM) for archival.

- 3 Log archival status updates provided to the DAM.

CORBA Integration

The Log Manager (LM) acts as a CORBA client. The CORBA server interfaces with which the LM interacts during service requests are defined in the CORBA integration document, and are referred to whenever possible. They will appear as the actual interface method name preceded by the server entity. For example, the notification represented by the LM sending the DAM a Log Archival Complete notification is DAM-LogArchDone.

10 **System variables**

For UNIX-based LM implementations the system variables are analogous to the UNIX shell environment variables (e.g. setenv in the csh) and can therefore be used for that purpose (e.g. setenv LMDIR <DirLoc>, for the csh)

15 CACHEDIR := DirLoc

The CACHEDIR variable defines the location of the logfile cache directory for the Security Device(s) (SD). The directory contains the logfiles of SD to be transferred to the Storage Manager (SM). This variable symbol is also used as a production in syntax definitions in this document.

LMDIR := DirLoc

The LMDIR variable defines the location of the LM run-time directory, which contains the configuration files, Security Device File (SDF), Log Transfer List (LTL), and Log Exception List (LEL) for the LM. This variable symbol is also used as a production in syntax definitions in this document.

CheckInterval

The CheckInterval variable defines the number of minutes between each check by the LM for new SD logfiles.

CleanupInterval

The CleanupInterval variable defines the number of days archived SD logfiles are kept by the LM. By default the number of days equals 3.

35 RetrievalInterval

The RetrievalInterval variable defines the number of hours an archived SD logfile will span. By default the number of hours equals 24 (i.e. 1 retrieval per day).

Configuration repository

- 5 The LM configuration repository at version 1.0 will be a configuration file. It is located on the LM host and uses the following syntax:

```
LMConfigRep := LMDIR "/" "LM.ini"
```

- In future versions of SDLRS, the LM configuration repository
10 may also be available via a database table. If the LM configuration repository is a database table, then it will use the following syntax:

```
LMConfigRep := "LMConfig" The LM validates that the $CACHEDIR directory exists.
```

- 15 1) The LM validates that the Security Device File , Log Transfer List, and the Log Exception List exists.
- 2) The LM checks the pending activity file to see if it has any pending actions to execute or restart.

20

Log collection Management

- The LM is responsible for transferring Security Device (SD) logfiles to the Storage Manager (SM) for archival. To perform this role within SDLRS, the LM must manage the
25 following aspects of the archival process:

- act as a temporary cache for logfiles in-transit for archival on the SM.
- transfer newly arrived SD logfiles to the SM for archival.
- 30 • notify the Data Analysis Manager (DAM) of SD logfiles that have been archived.
- maintain an exception list of SD that have not submitted logfiles for archival.

Log transfer Management

The LM manages the transfer of logfiles to the SM using a Security Device File (SDF) and a Log Transfer List (LTL).

Security Device File

The Security Device File (SDF) is a manually edited configuration file in \$LMDIR, and it contains information relevant to the archiving of SD logfiles, as well as in the data analysis of those logfiles. Each line in the file contains the following keys in order delimited by "white space":

- 10 • SD_Name // the FQHN, e.g.
 bcarh001.ca.nortel.com
- SD_Alias // e.g. fw-1-a-cc
- SD_Type // e.g. FW, SPM, etc.
- SD_SubType // e.g. EAGLE, RAPTOR4, etc.

15 An example line is provided below:

```
      bcarh001.ca.nortel.com        fw-1-a-cc FW    EAGLE
```

Log Transfer List

A Log Transfer List (LTL) is used to keep state of which SD logfiles require transferring to the Storage Manager for archival. Each entry in the LTL is a record consisting of the following fields in order, and delimited in this example by two asterisks:

- SD_Name
- SD_Alias
- 25 ■ SD_Type
- SD_Subtype
- Date
- Interval_Stamp
- Retrieval_Interval
- 30 ■ Log_Size // expressed in kilobits
- Compressed_Flag

51

- Data_Type
- Filepath // to be prepended by
\$CACHEDIR

An example LTL record for a firewall is given below:

```
5   bcarh001.ca.nortel.com**fw-1-a-
    cc**FW**EAGLE**19990910**00**24**895**y**ASCII**transfer/
    bcarh001/19990910-00/$LOGFILE
```

Log Exception List

A Log Exception List (LEL) is used to keep state of which
10 SD have submitted logfiles for archival during the logfile
retrieval interval. Each entry in the LEL is a record
consisting of the following fields in order, and delimited
in this example by two asterisks:

- Date
- 15 ■ Interval_Stamp
- SD_Name

An example LEL record for a SD is given below:

```
19990910**00**bcarh001.ca.nortel.com
```

Log Manager Interaction with a Security Device

20 The Log Manager (LM) is an independent process working in
conjunction with third-party Security Devices (SD) for the
purposes of archiving the SD logfiles in a managed,
centralized location.

The Security Device (SD) software must be configured such
25 that the following occurs on a daily basis :

- The SD logfile(s) must be transferred via an SD
administrative process to the appropriate directory on
the LM. An example UNIX directory representation is
provided : LMName:\$CACHEDIR/newlogs/\$SDNAME
30 /\$DATE.\$logfile
 - CACHEDIR is set in the LC.ini file
 - SDNAME is a sub-directory created in
\$CACHEDIR/newlogs by the SD administrative

51

process, which identifies the specific SD that created the logfiles.

■ \$DATE.\$logfile := \$DATE"."\$logfile

where:

5 \$DATE := the date specified in YYYYMMDD
ASCII format

\$logfile := the name of the logfile generated
by the SD

Preparing Security Device Logfiles for Archival

10 The LM cache directory (i.e. \$CACHEDIR) contains three
directories: "newlogs"; "transfer"; "archived". Newly
arrived logfiles from the SDs are found in the "newlogs"
directory under the appropriate SDName directory. These
logfiles must be prepared for transfer to the SM for
15 archival. The "transfer" directory contains new SD logfiles
which have been processed by the LM and are designated to be
transferred to the Storage Manager (SM) for archival. The
"archived" directory contains SD logfiles that have been
transferred to the SM, and that are cached for the period of
20 time specified by the \$CleanupInterval.
At a regular interval determined by the value of
\$CheckInterval, the LM checks the \$CACHEDIR/newlogs
directory for any newly created directories. When a new
directory is found, the logfiles contained in it are
25 processed as follows:

- Using the \$DATE obtained from the logfile name (i.e. \$DATE.\$LOGFILE), and the corresponding \$RetrievalInterval (e.g. 24 hrs.) for creating an IntervalStamp, the directory
30 \$CACHEDIR/transfer/\$SDNAME/\$DATE-\$IntervalStamp is created.
An example subdirectory created in \$CACHEDIR/transfer is provided below

■ \$CACHEDIR = /sdlrs/logarchive

53

```

      ■ $SDNAME    =    bcarh001
      ■ $DATE      =    19990910
      ■ $IntervalStamp =    00    // 24 divided by 24
        = 1 = "begin at midnight" = 00
5      ■ directory =
        /sdlrs/logarchive/transfer/bcarh001/19990910-
        00

```

- The logfiles contained in the \$SDNAME directory are then compressed (if not already compressed) and moved from \$CACHEDIR/newlogs/\$SDNAME/\$DATE.\$LOGFILE to the correct "transfer" directory \$CACHEDIR/transfer/\$SDNAME/\$DATE-\$IntervalStamp/\$LOGFILE
- A record entry for each logfile to be transferred to the SM via the NetFile Put method is then created in the Log Transfer List (LTL). (The NetFile methods are detailed in the CORBA integration document [MA1].)

Transfer of Logfiles for Archival

Immediately after a period of preparing any newly arrived SD logfiles for transfer to the SM for archival, the LM then transfers the logfiles associated with the entries in the Log Transfer List (LTL) to the SM using the NetFile Put method detailed in the SDLRS CORBA integration document [MA1]. Upon successful completion of the logfile transfer, the following events occur:

- A DAM-LogArchDone notification is sent to the DAM indicating that the SD logfiles are ready for analysis.
- move the logfile from the "transfer" sub-directory \$CACHEDIR/transfer/\$SDNAME/\$DATE-\$IntervalStamp/\$LOGFILE to the "archived" sub-directory \$CACHEDIR/archived/\$SDNAME/\$DATE-\$IntervalStamp/\$LOGFILE
- remove the corresponding record from the LTL
- remove the corresponding record from the LEL

Clean up of Logfiles after Archival

The LM keeps the SD logfiles that have been transferred to the SM for the duration specified in \$CleanupInterval. On a

daily basis, the LM removes any logfiles in the "archived" directory by doing the following:

- using the file creation date stamp of the directory \$CACHEDIR/archived/\$SDNAME/\$DATE-\$IntervalStamp as the logfile origin date, remove any directory (i.e. \$CACHEDIR/archived/\$SDNAME/\$DATE-\$IntervalStamp) and its contents that have exceeded the \$CleanupInterval in duration. This allows older logfiles which have been newly submitted to the LM to be archived for the desired duration.

Generating Logfile Archival Exceptions

The LM keeps state of the SD which have submitted logfiles to it during a \$RetrievalInterval period. At the beginning of each retrieval interval period, the LM performs the following tasks in order:

- Each record in the LEL represents a SD which did not submit its logfile(s) for an earlier interval period. The DAM is sent a notification for each LEL record indicating that it has not received the logfile(s) for the SD during the interval specified in the LEL record. This notification is done via DAM-Event as documented in the CORBA integration document [MA1].
- The LM appends to the LEL an LEL record for each SD listed in the Security Device File (SDF).

Concurrent Event Handling

There are no special requirements for concurrency on the LM.

Activity Status file

The Activity Status File (ASF) contains state information for various activities going on in the LM. For example, as each logfile transfer operation to the SM is initiated, the LM stores the event related information so that if the system crashes, it can restart any pending activity.

The pending activity file syntax is:

```
StatFile := LMDIR/" "LM.stt"
```

The syntax for each record is:

55

```

ASFEntry      := JobNumber Activity
JobNumber     := Integer[4]
Activity      := Log Prep | Log Transfer |
Archival Notification | Cleanup
Log Prep      := Status ";" DateTime ";" SDName
Log Transfer   := Status ";" DateTime ";"
LCMName ";" SDName ";" \
                LogAttributes;" ErrorStatus
Archival Notification := Status ";" DateTime ";"
SDName ";" LCMName ";" \
                LogRefs
Cleanup       := Status ";" DateTime
Status        := "n" // new but not acted on
                | "s" // started job
                | "c" // complete, just
cleaning up   | "f" // failed, just
cleaning up   | "r" // system failure,
job restarted
DateTime      := hh:mm:ss // UNIX date/time
(i.e. time())

```

Log Manager Event Logging

The LM logging uses syslog. Syslog should be setup with the following parameters:

```

void openlog(const char *ident = "LM", int logopt =
LOG_PID+LOG_NOWAIT,
int facility = LOG_USER);

```

- 5 A message will be issued when the following occurs:
 - 1) LM starts up, including command line parameters
 - 2) LM shuts down
 - 3) LM transfers log to SM using NetFile:Put method, including parameters
- 10 4) LM calls DAM -LogArchDone (log archival notification), including parameters
- 5) Significant state changes during log transfers (e.g. start, end, misc.)
- 15 6) Significant state changes during the creation of the Log Transfer List

55

- 7) LM calls DAM -Event during archival exception notifications
 - 8) Security related events
 - 9) When an error occurs
- 5 As much as possible the message part of the syslog() call should be in a machine parsable form.

Log Collector Manager

This section contains more detailed design information for the Log Collector Manager (LCM), which is a component of the Security Devices Log Reporting System (SDLRS) of the second
5 embodiment. The LCM is responsible for the co-ordination and retrieval of a number of Security Device (SD) operational logs, and the transferring of those logs to the Storage Manager (SM) for archival. In fulfilling this role, the LCM also has corresponding interactions with the Data
10 Analysis Manager (DAM) and Log Collector (LC) components of the SDLRS.

Design Representation

The intent of this section is to provide the architecture
15 and design of the LCM and not the implementation specifics of the LCM. For ease of understanding the LCM system configuration, files and tables detailed in the design, example content and records are provided to highlight key fields and information that are required by the LCM. The
20 actual implementation of the files and table content may vary.

Overview**Major Functions**

Obtains the logging system configuration from the Data
25 Analysis Manager (DAM) and propagates the configuration to the Log Collectors (LC) corresponding to the Security Devices (SD).

Notifies the LC to begin transferring the SD logfiles.

Pushes the cached SD logfiles to the Storage Manager (SM)
30 for archival.

Log archival status updates provided to the DAM.

CORBA Integration

The Log Collector Manager (LCM) acts as both a CORBA client and a CORBA server. The service requests that are defined in the CORBA integration document are referred to in this document whenever possible. They will appear as SR-n (where
 5 n is an integer) and preceded by the entity LCM. For example, the service request represented by the LCM receiving logging system configurations from the DAM is LCM SR-4.

Service Request Function Prototype

10 The service request functions are based on the service requests defined in the LCM entity interface in the SDLRS CORBA integration document

System Variables

For UNIX-based LCM implementations the system variables are
 15 analogous to the UNIX shell environment variables (e.g. setenv in the csh) and can therefore be used for that purpose (e.g. setenv LCMDIR <DirLoc>, for the csh)

CACHEDIR := DirLoc

The CACHEDIR variable defines the location of the logfile
 20 cache directory, which contains the logfiles of security devices in transit to the Storage Manager (SM). This variable symbol is also used as a production in syntax definitions in this document.

LCMDIR := DirLoc

25 The LCMDIR variable defines the location of the LCM run-time directory, which contains the: configuration files; Log Collector Table; Security Device Table. This variable symbol is also used as a production in syntax definitions in this document.

30 Configuration Repository

The LCM configuration repository at version 1.0 will be a configuration file. It is located on the LCM host and uses the following syntax:

```
LCMConfigRep := LCMDIR "/" "LCM.ini"
```

- 5 In future versions of SDLRS, the LCM configuration repository may also be available via a database table. If the LCM configuration repository is a database table, then it will use the following syntax:

```
LCMConfigRep := "LCMConfig"
```

10 Initialization

The LCM queries the Data Analysis Manager (DAM) for its Security Device (SD) list, and the log retrieval and cleanup interval configurations for the different device types.

- 15 The LCM validates that the Log Collector Table (LCT) exists, and is populated with the LC list received from the DAM.

The LCM validates that the Security Device Table (SDT) exists, and is populated with the corresponding SD to LC data.

- 20 The LCM notifies the Log Collectors (LC) of the log retrieval and cleanup interval configurations.

The LCM checks the pending activity file to see if it has any pending actions to execute or restart.

Log Collection Management

- 25 The LCM is responsible for retrieving Security Device (SD) logfiles from their associated Log Collectors (LC) and then sending them to the Storage Manager (SM) for archival. To perform this role within SDLRS, the LCM must manage the following aspects of the archival process:
- manage a dynamic list of SD that could potentially change on
- 30 a daily basis.
- provide the LC, for which the LCM is responsible, with the retrieval and cleanup intervals.

notify the LC, for which the LCM is responsible, to begin logfile transfers for the SD associated with the LC. act as a temporary cache for logfiles in-transit for archival on the SM.

- 5 notify the Data Analysis Manager (DAM) of SD logfiles that have been archived.

notify the DAM that all SD logfiles associated with the LC list have been archived.

Log Collector and Security Device Associations

- 10 A Log Collector (LC) manages the log archival for one or more Security Devices (SD) depending on the SD architecture. For example, there is a one-to-one relationship between LC and SD for Raptor firewalls, but there can be a one-to-many relationship between LC and Contivity Extranet Switches (CES), since a LC cannot be co-located with a CES at the time of writing this document. Therefore given this relationship of possible one-to-many SD to a LC, the LCM must manage which LC is responsible for which SD.

Log Collector List

- 20 The Log Collector (LC) List is the association of SD to LC generated by the Data Analysis Manager (DAM). From this LC List, the LCM manages the transition of SD logfiles to the Storage Manager (SM) for archival.

Acquiring the Log Collector List

- 25 On a daily basis, the LCM contacts the DAM for the list of LC for which the LCM is responsible for the day's log collection. Since the list of LC for which a LCM is responsible is of a potential dynamic nature, the LCM manages each day's LC list in a separate Log Collector Table and Security Device Table. The notification that the LCM sends the DAM to acquire the LC list is detailed in the DAM
- 30

SR-4 (Obtain LC List) in the SDLRS CORBA integration document [MA1].

Log Collector Management Tables

The LCM manages the LC to SD relationship using two tables:

- 5 Log Collector Table (LCT); Security Device Table (SDT).

These tables are created using the data contained within the LC List. At the time that the LC List is retrieved from the DAM, the following events occur:

- the LCM checks for a valid LCT and SDT , and if they exist
- 10 writes the contents of the LCT and SDT to syslog as an error. The tables are then renamed with "WARNING" prepended to the table name.
- the LCM creates a new LCT.
- the SDT is created as the LCM sends "logfile transfer begin"
- 15 notifications to the LC, and receives back the expected number of intervals of SD logfiles that will be archived.

Log Collector Table

- A Log Collector Table (LCT) is used to maintain the status
- 20 of : LC system configuration notifications; LC logfile transfer notifications; SD archival complete; LC archival complete.

Log Collector Table Naming Convention

The LCT name syntax is as follows:

- 25 LCTab.Date := "LCTab."Date
- Date := MMDDYYYY
- MM := (01|02|03|04|05|06|07|08|09|10|11|12)
- DD := (01|02|03|04|05|06|07|08|09|10|11|...|20|21|...|30|31)
- 30 YYYY := Year expressed in string format

Log Collector Table Format

The first 7 keys in the LCT define the characteristics of the table. These table characteristics are as follows:

```

LCT Date           // Date of the LCT creation
LC Count           // Number of LC to manage
5  SD Count         // Number of SD with logfiles to archive

```

```

LC Config Notification Count // Number of LC provided with
system configuration
SD Logfile Transfer Count    // Number of SD begin-
10 transfer-notifications
SD Archival Complete Count   // Number of SD with logfiles
successfully archived
LC Archival Complete Count   // Number of LC complete
Each subsequent entry in the LCT is a record consisting of
15 the following fields in order, and delimited by two
asterisks (i.e. '**'):

```

```

LC_Complete_Flag
Config_Sent_Flag
LC_Name
20 LC_IP_Address
   "SD1"("","SD2") [...]           // list of SD managed by
the LC
   "Log_Transfer_Begin1"("","Log_Transfer_Begin2") [...] //
flags for SD list
25 "Archival_Complete1"("","Archival_Complete2") [...] // flags
for SD list

```

where:

```
SD"n" := {SD_Name, SD_IP_Address}
```

An example LCT record is given below :

```
30 n**y**fw-1-a-cc**47.150.48.2**bcarh001,47.150.48.2**y**n
```

The example LCT record indicates :

LC is still active

System configuration has been sent to the LC

LC name

LC IP address

SD Name, SD IP address

- 5 Request to begin log transfer for SD Name has been sent to the LC

Archival notification to the DAM has not been sent

Security Device Table

- 10 A Security Device Table (SDT) is used to maintain the status of : logfile transfer start time; logfile transfer current time; number of logfile transfer sessions expected; number of logfile transfer sessions completed; SD logfile attributes

- 15 Security Device Table Naming Convention

The SDT name syntax is as follows:

SDTab.Date := "SDTab."Date

Date := MMDDYYYY

MM := (01|02|03|04|05|06|07|08|09|10|11|12)

- 20 DD := (01|02|03|04|05|06|07|08|09|10|11|...|20|21|...|30|31)

YYYY := Year expressed in string format

Security Device Table Format

- 25 The first 5 keys in the SDT define the characteristics of the table. These table characteristics are as follows:

SDT Date // Date of the SDT creation

Logfile Transfer Start Time // Timestamp - first logfile transfer completed

- 30 Logfile Transfer Current Time // Timestamp - last logfile transfer completed

Logfile Transfer Session Count // Number of logfile
transfer sessions expected
Logfile Transfer Complete Count // Number of logfile
transfer sessions completed

5

Each subsequent entry in the SDT is a record consisting of
the following fields in order, and delimited by two
asterisks (i.e. '*'):

LC_Name

10 LC_IP_Address

SD_Name

SD_IP_Address

SD_Type

Logfile_Date

15 Retrieval_Interval

"Logfile_Type 1"(", "Logfile_Type 2") [...]

"Logfile_Time 1"(", "Logfile_Time 2") [...]

LogCacheDir

The LogCacheDir is unique for each entry in the table, and

20 is the cache location within the \$CACHEDIR for a security
device's logfiles on that day. The format of the

LogCacheDir is provided below :

LogCacheDir := Logfile_Date/SD_Name/

The logfiles within LogCacheDir reflect the Logfile_Type and

25 Logfile_Time in the following format :

Logfile_Type1"-Logfile_Time1"-log

An example SDT record for a firewall is given below:

fw-1-a-cc**47.150.48.2**bcarh001**47.150.48.2**fw**

19990804**24**raptor4**00**19990804/bcarh001

30 An example of the logfile within the LogCacheDir is given
below:

19990804/bcarh001/raptor4-00-log

Log Collector System Configurations

The LCM is responsible for retrieving from the DAM the system configurations relevant to Log Collectors (LC) for the Security Devices (SD), and pushing these system configurations to the LC assigned to the LCM for that particular day.

Obtaining Configurations from the Data Analysis Manager

On a daily basis the LCM sends a notification to the DAM to acquire the SDLRS configuration settings for retrieval and cleanup intervals, which the LCM then stores in a file in the LCM run-time directory. This notification is detailed in the DAM SR-5 (Obtain Configuration Information) in the SDLRS CORBA integration document [MA1].

Pushing Configurations to the Log Collectors

The LCM pushes the retrieval and cleanup interval configurations to each Log Collector (LC) with an entry in that day's Log Collector Table (LCT). The configuration notification is detailed in the LC SR-2 (Set Configuration Information) in the SDLRS CORBA integration document [MA1].

Transfer of Logfiles for Archival

Transferring Logfiles from the Log Collectors

The LCM notifies the LC to begin transferring logs to the LCM through the LC SR-3 (Transfer Log Information) notification detailed in the SDLRS CORBA integration document [MA1]. The LC returns to the LCM the number of interval periods (e.g. default interval period equals 1 day) of SD logs that the LC intends to transfer to the LCM. The logfile date(s) associated with the interval period(s) is passed as part of the parameter list. The LCM upon receiving the intended number of logfile retrieval intervals

for a SD creates a Security Device Table entry for each retrieval interval with the corresponding date associated with the retrieval interval.

After the return of the LC SR-3 notification, the LCM can
 5 expect the transferring of logfiles from the LC via LCM SR-2 (Transfer Log to LCM) for each corresponding interval period. An example is provided below:

interval period = 24 hrs = 1 day

number of interval periods of SD logs to transfer = 3 days

10 number of logfiles per interval period for this SD = 2
 logfiles

LCM SR-2 called for: day1; day2; day3

number of logfiles transferred in each LCM SR-2 call = 2
 logfiles

15 When a LCM SR-2 (Transfer Log to LCM) is initiated, the corresponding SD logfiles are cached in the \$CACHEDIR (See the "Security Device Table Format" section for cached logfile naming conventions.) At the successful completion of LCM SR-2, the LCM updates the appropriate SD record in
 20 the SDT for the corresponding interval period.

Transferring Logfiles to the Storage Manager

As the LCM receives logfiles from a LCM SR-2 call they are stored in the appropriate directory in \$CACHEDIR. Once the
 25 transaction is complete and the SDT table updated, the logfiles are then transferred to the SM using SM SR-2 (Transfer Log to SM) detailed in the SDLRS CORBA integration document [MA1]. Upon successful completion of SM SR-2, the following events occur:

30 Security Device Table (SDT) characteristics are updated, and the corresponding SD entry in the SDT removed.

A DAM SR-1 (Log Archival Complete) notification is sent to the DAM indicating that the SD logfiles are ready for analysis.

5 The Log Collector Table (LCT) characteristics are updated, and the corresponding LC entry in the LCT updated.

If LCM log archival is now complete for all SD, then a DAM SR-1 (Log Archival Complete) notification is sent to the DAM indicating that the LCM has completed all logfile archivals, and the day's LCT and SDT are removed after writing the
10 table characteristics to the system log.

Logfile Archival Notifications to the Data Analysis Manager
The LCM sends logfile archival notifications to the DAM in the case where a SD logfiles have been successfully archived to the SM, and in the case where all the SD assigned to a
15 LCM have successfully had their logfiles transferred to the SM for archival.

Notification of Security Device Log Archival Complete
Once the logfiles associated with an SD for a particular interval period have been transferred to the SM for
20 archival, the LCM sends an archival complete notification to the DAM. This notification is detailed in the DAM SR-1 (Log Archival Complete) in the SDLRS CORBA integration document [MA1]. The effect of the notification is for the DAM to begin the data analysis of the SD logfiles. For more
25 information see the SDLRS DAM design document [MA2].

Notification of Log Archivals Complete
Once all of the SDs designated to the LCM by the DAM have had their logfiles archived on the SM, the LCM sends an archival complete notification to the DAM. This
30 notification is detailed in the DAM SR-1 (Log Archival Complete) in the SDLRS CORBA integration document [MA1].

The effect of the notification is to inform the DAM that the LCM has completed log archivals for that interval period.

Concurrent Event Handling

- The nature of the LCM is that it will not have to deal with
- 5 a large number of transactions-per-second (tps), but rather that the majority of LCM transactions will be of a long-lasting nature due to event-caused, prolonged, disk-related activity. Given these system specifics, the LCM must be able to handle multiple concurrent events. For example, a
- 10 "transfer log to LCM" notification from a LC (LCM SR-2) can arrive from a LC at the same time as another LCM SR-2 is received from a different LC. Each of these events could potentially result in substantial disk activity given that logfiles can be of substantial size.
- 15 The most efficient means of handling concurrency in this scenario is through lightweight threads. In the worst case of the LCM running on a single processor system, the overhead involved in thread creation and in context switching between threads is minimal when compared to the
- 20 latency times associated with disk accesses. In the best case, of multiple disk controllers, and multiple processors on a SMP (symmetrical multi-processing) LCM system, threads would be able to concurrently process on different processors/disk controllers. For these reasons, the LCM
- 25 should be implemented using threads rather than by an event loop.

Activity Status File

- The Activity Status File (ASF) contains state information
- 30 for various activities going on in the LCM. For example, as each logfile transfer notification from a LC is received,

the LCM stores the event related information so that if the system crashes, it can restart any pending activity. The information in the stat file can be displayed via LCM SR-1.

5 The pending activity file syntax is:

StatFile := LCMDIR"/" "LCM.stt"

The syntax for each record is:

ASFTEntry := JobNumber Activity

JobNumber := Integer[4]

10 Activity := Sys Config | Cache | SM Transfer |

Archival Notification

Sys Config := Status";" DateTime ";" LCName ";"

ConfigInfo

Cache := Status ";" DateTime ";" SDName ";"

15 LCName ";" \

";" LogRefs

SM Transfer := Status ";" DateTime ";" SDName ";"

LCName ";" \

";" LogRefs

20 Archival Notification := Status ";" DateTime ";" SDName

";" LCName ";" \

";" LogRefID ";" ErrorStatus

Status := "n" // new but not acted on

| "s" // started job

25 | "c" // complete, just cleaning up

| "f" // failed, just cleaning up

| "r" // system failure, job

restarted

DateTime := Base16 // UNIX date/time (i.e. time())

30 in base 16

Base16 Table

The table for the base16 representation is:

```

Base16Table    :=    "a"    // for 0
                  |    "b"    // for 1
5              |    "c"    // for 2
                  |    "d"    // for 3
                  |    "e"    // for 4
                  |    "f"    // for 5
                  |    "g"    // for 6
10             |    "h"    // for 7
                  |    "I"    // for 8
                  |    "j"    // for 9
                  |    "k"    // for 10
                  |    "l"    // for 11
15             |    "m"    // for 12
                  |    "n"    // for 13
                  |    "o"    // for 14
                  |    "p"    // for 15

```

Log Collector Manager Event Logging

20 The LCM logging uses syslog. Syslog should be setup with the following parameters:

```

void openlog(const char *ident = "LCM", int logopt =
LOG_PID+LOG_NOWAIT,
int facility = LOG_USER);

```

25

A message will be issued when the following occurs:

LCM starts up, including command line parameters

LCM shuts down

LCM receives LCM SR-1 (DAM requesting status info),

30 including SR parameters

LCM receives LCM SR-2 (caching of log from LC), including SR parameters

- LCM receives LCM SR-3 (LC requesting configuration info),
including SR parameters
- LCM receives LCM SR-4 (set configuraton information),
including SR parameters
- 5 LCM calls DAM SR-1 (log archival notification), including SR
parameters
- LCM calls DAM SR-4 (obtain LC list), including SR parameters
- LCM calls DAM SR-5 (obtain system configuration info),
including SR parameters
- 10 LCM calls LC SR-1 (obtain LC status), including SR
parameters
- LCM calls LC SR-2 (set configuration info), including SR
parameters
- LCM calls LC SR-3 (transfer log info), including SR
- 15 parameters
- LCM calls SM SR-2 (log transter to SM), including SR
parameters
- Significant state changes during log transfers (e.g. start,
end, misc.)
- 20 Significant state changes during Log
- Significant state changes during the creation of Log
Collector Management Tables
- Security related events
- When an error occurs
- 25 As much as possible the message part of the syslog() call
should be in a machine parsable form.
- For Future Study
- A tool to enter and modify LCM configuration information.
- The possibility of the LCM specifying date ranges of
- 30 logfiles to be transferred from the Log Collectors.

Additional description of operation of the Log Collector
Manager (LCM)

The number of LCMs in the system may be one or more with the responsibility of an LCM being that of co-ordination and
5 retrieval of a number of different SD operational and system performance logs. The LCM contacts the Data Analysis Manager (DAM) on a 24 hour basis to acquire its assigned SD identification list, and the log retrieval and cleanup configuration settings for the system. During the log
10 retrieval process, the LCM performs the following: initiates the connection to the LC; provides system configuration updates for log retrieval and log cleanup frequencies to the LC; securely pulls the SD log(s). Logs that have been securely pulled, are then securely pushed to the Storage
15 Manager (SM) for archival with the LCM providing for each log transfer the device type, date, and SD name to the SM. Upon the transfer of an SD log(s) to the SM, the DAM is notified of the job status, and in the case of errors the error code. Upon completion of all log transfers, the LCM
20 notifies the DAM with an "end of transactions" notification.

The following lists references to the LCM in other processes taken from the SDLRS design description above.

A LC may be identified for each SD, or a group of SDs
25 depending on the SD technology. In either case, the LC is responsible for the following during the log retrieval process: accessing the SD log(s), securely (i.e., authentication, privacy) transferring the SD log(s) to the Log Collection Manager (LCM); cleanup of transferred log(s)
30 on the SD.

As part of the log transfer process, the LCM begins a secure log transfer to the SM with the date, device type, and SD name for the log being transferred.

SDs having been assigned hostnames/aliases that indicate
5 their security function and geographical location are then categorized into SD lists associated with the LCM(s) in the system.

When an LCM contacts the DAM, the LCM is provided with the log retrieval, and log cleanup configurations, as well as
10 the SD list for which that LCM is responsible.

As the LCM(s) notify the DAM of the successful transfer of SD logs, the DAM then contacts the SM for the location of the SD log such that the appropriate data filter can be applied to the log.

15

Storage Manager

This section contains the detailed design information for the Storage Manager (SM), which is a component of the Security Devices Log Reporting System (SDLRS). The SM is responsible for the management of physical log archival storage/access, and the corresponding interaction with the Data Analysis Manager (DAM) and Log Collector Manager (LCM) components of the SDLRS.

Design Representation

The intent of this section is to provide the architecture and design of the SM and not the implementation specifics of the SM. For ease of understanding, the SM system configuration detailed in the design is provided to highlight key fields and information that are required by the SM. The actual implementation of the content may vary.

Overview

Major Functions of the Storage manager

Receives Security Device (SD) logs from the Log Collector Manager (LCM) for system archival.

Management of online and offline log archivals, and the transition of logs from online to offline status.

Provides the Data Analysis Manager (DAM) with access to SD logs upon request.

Provides the DAM with access to the SM log archival tables upon request.

CORBA Integration

The Storage Manager (SM) acts as both a CORBA client and a CORBA server. The CORBA interface for the SM is defined in the SDLRS CORBA integration document. The service requests that are defined in the CORBA integration document are referred to in this document whenever possible. They will appear as the actual interface method name preceeded by "SM-

". For example, the service request represented by the SM providing logfile information to the DAM is SM-GetLogInfo.

Service Request Function Prototype

The service request functions are based on the service requests defined in the SM entity interface in the SDLRS
5 CORBA integration document [MA1].

System Variables

For UNIX-based SM implementations, the system variables are analogous to the UNIX shell environment variables (e.g.
10 setenv in the csh) and can therefore be used for that purpose (e.g. setenv SMDIR <DirLoc>, for the csh).

ARCHIVEDIR := Dirloc

The ARCHIVEDIR variable defines the location of the directory used to archive online logs according to their
15 security device type.

RESTOREDIRE := DirLoc

The RESTOREDIRE variable defines the location of the SM restored logfile directory. This is the location where offline logs are to be restored to disk.

20 SMDIR := DirLoc

The SMDIR variable defines the location of the SM run-time directory, which contains the: configuration files; online and offline archival tables; log reference tables; restored log archival table; potentially other configuration files.

25 This variable symbol is also used as a production in syntax definitions in this document.

SMDIRBKP := DirLoc

The SMDIRBKP variable defines the location of the SM configuration backup directory located on a different disk
30 partition than that of the SMDIR directory. The primary reason for SMDIRBKP is to maintain a second copy of the log archival tables which are of a highly dynamic nature.

Configuration Repository

The SM configuration repository at version 1.0 will be a configuration file. It is located on the SM host and uses the following syntax:

5 SMConfigRep := SMDIR "/" "SM.ini"

In future versions of SDLRS, the SM configuration repository may also be available via a database table. If the SM configuration repository is a database table, then it will use the following syntax:

10 SMConfigRep := "SMConfig"

Initialization

The SM queries the DAM for the log archival interval configurations for the different device types.

The SM validates that the appropriate online and offline
15 archival tables exist based on actual device_types (i.e. EntityTypes) for currently archived logfiles.

The SM checks the pending activity file to see if it has any pending actions to execute or restart.

The SM performs any necessary log cycling from on-line
20 status to off-line status, and from off-line status to N/A status.

Log Archival Tables

A logfile has an archival status of either "online" or "offline". This archival status must be maintained along
25 with other logfile attributes for as long as the logfile exists within the system. To do this, an archival table is maintained for each type of security device's logs that are managed by the SM. The two exceptions to this are: 1) export controlled devices; 2) logfiles that have been
30 previously offlined, and then restored. In each of these cases, separate tables are maintained, however, the table and record format in each case is identical. Maintaining a

separate archival table for each security device type,
allows for greater scalability of the system, which in turn
will enhance the performance of table and logfile
retrievals on a large system with many different types of
5 security devices.

Archival Table Naming Convention

The security devices archive table name syntax is as follows
for non-export-controlled security devices:

```
EntityTypeArchTbl := EntityType Hyphen "ArchTbl"
10 EntityType      := as defined under "Modules" -
CORBA integration [MA1]
```

The archive table name syntax for export-controlled security
devices is as follows:

```
ExpEntityTypeArchTbl := "Exp" hyphen EntityType
15 hyphen"ArchTbl"
EntityType           := as defined under "Modules" -
CORBA integration [MA1]
```

The archival table name syntax for restored "offline"
security device logfiles is as follows:

```
20 ResEntityTypeArchTbl := "Res" hyphen EntityType hyphen
"ArchTbl"
EntityType           := as defined under "Modules" -
CORBA integration [MA1]
```

25 Creation of New Archival Tables

The security devices for which archival tables exist are
defined within the system by the 'EntityType' , as defined
under the "Modules" section in the CORBA integration
document [MA1]. The SM will create a new security device
30 archival table if one does not already exist under the
following conditions:

Upon receiving a logfile from an LCM, the security device type is extracted from the security device hostname alias, and validated against known "Entity Types". If this is the first instance of a valid security device type log archival, then an archive table is created for the security device type.

An event which leads to the creation of a security device archival table will result in an alarm being generated and sent to the DAM via DAM-Event as documented in the CORBA integration document [MA1].

Archival Table Format

Determining Security Device Type

The security device type associated with a table is determined by parsing the archive table name. For example, the firewall archive table name would be "FW-ArchTbl". The export controlled firewall archive table name would be "Exp-FW-ArchTbl".

Archive Table Characteristics

An archive table is a chronologically ordered table based on the date and time of the actual log archival occurring on the SM. For this reason, no inserts to the table are required, as all new records will be appended to the table. The table is of fixed record size.

The table contains records for logfiles with online status as well as offline status

The first two records of an archive table are reserved for table specifics. These specifics should include as a minimum:

Table offset for the first "Offline" archival record, and the "logfile date" associated with the archival record
Table offset for the first "Online" archival record, and the "logfile date" associated with the archival record

The records between the first archival record with an "Offline" status and the first archival record with an "Online" status, are logfiles deemed Offline.

The records following the first archival record with an "Online" status are logfiles deemed "Online".

One archive record exists per archival directory regardless of the number of logfiles contained in that archival directory. The number of logfiles expected within an archival directory to be determined by the logfile retrieval-per-day interval.

Archive Record Format

A log archival record consists of the following required fields:

```

Directory_Reference_ID    // unique path of the directory
15 containing a logfile(s)
Logfile_Date              // date of logfile created by
security device
Online_Status             // either Online, Offline, or Restored
Logfile_Type              // correlates to the type used by the
20 data filter
Retrievals_Per_Day        // correlates to the # of logfiles
per unique directory
SD_Name                   // security device alias name
Data required for transaction audit purposes. This data
25 would be relatively static for a device and hence may be
better accessed through the SDLR logging. However, they are
included here as optional fields within an archival record:
SD_IP_Address             // security device's IP address
LC_Name                   // the name of the Log Collector
30 LCM_Name                // the name of the Log Collector Manager

```


Archive Record Example

The following is an example of a log archival record for a non-export-controlled firewall including the required and optional fields in the record:

```

5  Directory_Reference_ID    :=    "unique hash of DirPath" where
    Dirpath =
    $ARCHIVEDIR/Main/Wk_Of_The_Month/Device_Type/Logfile_Date/SD
    _Name
    Logfile_Date            =      19991210
10  Online_Status           =      "Enum type for Online"
    Logfile_Type            =      EAGLE
    Retrievals_Per_Day      =      1
    SD_Name                 =      fw-1-n-cn
    SD_IP_Address           =      47.1.2.3
15  LC_Name                 =      <hostname>
    LCM_Name                =      <hostname>

```

Logfile References

A "Logfile Reference" is used to uniquely identify a logfile archived on the SM. "Logfile References" are utilized by the SM for tracking logfiles requested by the DAM in either automated analysis mode or custom analysis mode.

Each "Logfile Reference" consists of a "Directory Reference ID" component and a "Logfile Name" component. Taken together these components comprise a Logfile Reference ID, which uniquely identifies a logfile archived on the SM.

Logfile Reference ID

Logfile Reference IDs are used by the SM in its communication (Open Method) between the SM and LCM objects, between the LCM and DAM objects (interface DAM-LogArchDone), and in its communication (Open Method and the interface SM-GetLogInfo) between the SM and DAM objects. The two parts

which make up a "Logfile Reference ID" are the "Directory Reference ID" and the "Logfile Name" .

Directory Reference ID

The Directory Reference ID is a unique "hash number" based
 5 on the archival directory where a logfile will reside.
 Depending on the hashing algorithm used, the unique "hash
 number" may be of varying lengths. However, the 'hash
 number' should not exceed 128 bits so that it does not
 negatively impact the size of archival table record entries
 10 where the Directory Reference ID is stored.

The archival directory to be hashed is of the following
 format:

E.g., Export-controlled Security Device directory

\$ARCHIVEDIR/~~ExpCt1~~/Wk_Of_The_Mon/Device_Type/Logfile_Date/SD
 15 _Name

E.g., Non-export-controlled Security Device directory

\$ARCHIVEDIR/~~Main~~/Wk_Of_The_Mon/Device_Type/Logfile_Date/SD_N
 ame

Logfile Name

20 The "Logfile Name" component of a "Logfile Reference" is
 comprised of the "Logfile_Type" associated with a logfile,
 and a sequencing number. The boundaries of potential
 sequencing numbers determined by the "Retrievals_Per_Day",
 and the existence of logfiles with sequencing numbers
 25 already contained within the archival directory.

The "Logfile Name" is of the following format:

Logfile_Type hyphen <sequence number> hyphen "log" period
 <compression tag>

E.g Firewall logfile of type EAGLE and a retrieval interval
 30 of 2 provides up to two possible "Logfile Names". With the
 GNU compression tag being used in this example, the two
 potential "Logfile Names" are:

EAGLE-1-log.gz

EAGLE-2-log.gz

Logfile Reference ID Format

- 5 A logfile is uniquely identified by combining the "Directory Reference ID" with a "Logfile Name". An example is given below:

E.g. Logfile Reference ID for a unique firewall logfile of type EAGLE and a Retrieval Interval of 1

- 10 <16 bit hash of archival directory> .EAGLE-1-log

E.g. Logfile Reference ID for all logfiles of a firewall of logfile type EAGLE and a Retrieval Interval of 4

<16 bit hash of archival directory>

- 15 Directory Reference ID Index

A "Directory Reference ID" index is maintained for each archival table. As each "Directory Reference ID" identifies a unique archival record, the index is used to facilitate archival record lookups by associating the unique
20 "Directory Reference ID" to the offset in the table where the archival record is stored.

Log Archival

Disk Archival

New logs for archival are received from a LCM via the

- 25 Netfile methods (i.e. Open, Put, Close) defined in the SDLRS CORBA Object Architecture document [MA1]. The process of archiving a log is detailed below:

The SM checks for enough available disk space to receive the log in its entirety.

- 30 Based on the security device type, logfile date, and device alias, the appropriate archival directory is created if required and the logfile is received. (See the Logfile

References section for the archival directory and logfile name formats.)

Upon receipt of the logfile(s) for the security device, a new entry is created in the applicable security device

- 5 Archival Table if this is the first logfile to be stored in the archival directory.

Tape Archival

- With online data archiving, the potential exists for large volumes of data to reside on the SM archival disks. This
- 10 data can be broken down into dynamic data (e.g. newly archived logs) and static data (e.g. previously archived logs). To reduce the cost associated with tape archivals, it is therefore useful to architect the log archival directories/disks in such a manner that full backups of
- 15 static data occur only once, which is at the time that the data volume becomes static. Incremental backups are then done on a nightly basis to backup any new logs archived that day.

- Facilitating Low Cost Tape Archivals by Archival Directory
- 20 The SM will have incremental tape backups on a nightly basis and full backups of static archival directories/disks on a weekly basis. To facilitate this functionality, the online log archival filepaths will reflect the week of the month that the logfiles were generated. The weeks are defined as
- 25 follows:

```

wk1      :=  days 1-7
wk2      :=  days 8-14
wk3      :=  days 15-21
wk4      :=  days 22-28 + days 29,30,31 as required

```

- 30 Some example log archival filepaths are as follows:

1) Logfile_Date = 19990804; Security Device Type = fw

```
Logfile_Path = $ARCHIVEDIR/wk1/fw/19990804/fw-1-n-cn/EAGLE-
1-log.gz
```

```
Logfile_Date = 19990812; Security Device Type = fw
```

```
5 Logfile_Path = $ARCHIVEDIR/wk2/fw/19990812/fw-1-n-cn/EAGLE-
1-log.gz
```

```
3) Logfile_Date = 19990829; Security Device Type = fw
```

```
Logfile_Path = $ARCHIVEDIR/wk4/fw/19990829/fw-1-n-cn/EAGLE-
10 1-log.gz
```

A weekly full backup tape archival can then be setup to archive \$ARCHIVEDIR/wk[n] (where n=[1|2|3|4]) on a rotating basis. The rotation is based on the full backup to be done of the archival directory for the preceeding week. The effect of this rotation is to reduce the incidence of reoccurring full backup tape archivals of static data. An example of a weekly full backup scenario is given below: Sunday, August 31 full backup scheduled

```
20 day of backup = 31; days/wk = 7
```

```
31 div 7 = 4
```

```
preceeding week = (4 -1) = 3 ; (In the case where the
preceeding week is less than or equal to 0, the preceeding
week becomes equal to 4. )
```

```
25 full backup of $ARCHIVEDIR/wk3 to tape
```

Accessing Logs and Log Archival Tables

Logfiles once they are stored on the SM can be accessed via the DAM interface to the SM either as part of the automated analysis mode, or the logfiles can be accessed by the WAS via the DAM interface to the SM as part of the custom analysis mode. Logfile Archival Tables can also be accessed by the WAS via the DAM interface to the SM.

Accessing Logs

Automated Analysis Mode

In the automated analysis mode, a Directory Reference ID (DRID) and a log Archival Table entry are created at the
5 time that the LCM successfully completes its transfer of a SD logfile(s) to the SM. The Logfile Reference ID (LRID) are passed back to the LCM, so that they may be passed to the DAM as part of the LCM log availability notification process (i.e. DAM-LogArchDone). The DAM then will provide
10 the LRID as part of a log retrieval request to the SM.

Custom Analysis Mode

Obtaining Logfile Information

In the custom analysis mode, a request is received from the DAM (i.e. SM-GetLogInfo) in which logfile information is
15 passed in the request. The SM then returns the requested logfile records from the associated security device Archival Tables.

Logfile Retrieval

An actual logfile retrieval request in custom analysis mode,
20 will provide a Logfile Reference ID (LRID), which can uniquely identify a logfile for retrieval or a set of logfiles applicable to a security device for a particular date. The LRID for a unique logfile contains both a DRID and Logfile Name component. The LRID for the logfiles of a
25 specific date may contain only a DRID component.

As it is possible in the custom analysis mode to have several concurrent requests for a particular logfile at one time, the SM must manage each log transaction independently from another.

30 Log Archival Tables

The retrieval of archival tables is based on three factors: security device type; whether the devices are export-

controlled or not; whether the archival tables are for restored logfiles or not. A request from the DAM to return archival table entries is made through the SM interface SM-GetLogInfo as defined in the CORBA integration document

5 [MA1].

Transitioning the Archival Status of Logs

Logfiles are archived on the SM for a specified online archival duration (e.g. by default the duration is three

10 months). After the online archival period, a logfile record is tracked for the duration of the offline archival period. The time of the offline archival period being dependent on whether or not the security device is an export-controlled device. After the offline archival time period has

15 transpired, the record of a logfile is no longer tracked.

Transitioning Occurrence

The transistioning of archival status from offline to N/A is done on a nightly basis, as it is essentially an archival table manipulation operation only. The transistioning of

20 archival status from online to offline is done on a weekly basis rather than a daily basis. The advantage of this weekly processing is the ability to have archival transition occur on a day where log data volume is expected to be lower (i.e. Sunday) than during the rest of the week. The

25 disadvantage to weekly processing is that approximately 86% of the logs will be archived online for an average 3 days longer than the configured monthly archival rate, which will result in a slight increase in the disk space required for online archival. For example, using the default three month

30 online archival rate (90 days), an extra three days would necessitate an approximate 4% increase in disk space requirements.

Offline to N/A Status

Once a day, the SM transitions logfile records from offline status to N/A status. The SM does this in the following manner:

- 5 The first record of an archive table contains the offset of the first offline archival record.

Beginning with the first offline archival record, the SM sequentially examines the "logfile date" of each archival record to see if it meets the offline archival duration
10 criteria.

The offset of the first archival record which meets the offline archival duration criteria is saved along with the "logfile date" to the first record of the archival table.

Online to Offline Status

- 15 Once a week, the SM transitions any logfile archival records that exceed the online archival duration to offline status. In the process, the SM also compresses the archival table by removing archival records that have exceeded the offline archival duration period, as well as
20 rebuilds the Directory Reference ID index. The SM does this in the following manner:

The first record of an archival table contains the offset of the first offline archival record. The second record of an archival table contains the offset of the first online

- 25 archival record.

The Directory Reference ID index associated with the archival table is recreated at the time of creating the newly compressed archival table.

- Beginning with the first offline record, the archival table
30 is rewritten. Logfile archival records are written to a temporary table with an updated offline status up to the first online archival record. (The offset of the first

online archival record is provided in the second record of the archive table.)

Each subsequent archival record is then examined as to whether the 'logfile date' has exceeded the online archival duration period. If it has, and the 'logfile date' directory for that security device type (i.e. EntityType) exists, the 'logfile_date' directory is removed. The archival record is then written to the temporary table with an offline status.

10 The offset of the first archival record whose "logfile date" meets the online archival duration criteria is saved to the second record of the archival table, and the record written to the temporary table with an online status.

All subsequent records are written to the temporary table as is with no archival duration comparisons required.
15 The temporary table replaces the current table.

Restored Offline Logs

Restoring a Log

20 Restored logfiles from backups are differentiated from logfiles that are still online in order to make it easier to track them from an administrative perspective. Therefore, log restores will be restored to the RESTORED/Log directory.

25 Processing Log Restores

The SM on a hourly basis checks the RESTORED/Log directory for newly restored logfile directories. For each restored logfile directory, an archival record is created in the applicable "restored" archival table, (see Log Archival
30 Tables section for more details) and the logfile directory is moved to the appropriate RESTORED directory. An example is provided below:

Regular archival path:

\$ARCHIVEDIR/~~Main~~/Wk_Of_The_Mon/Device_Type/Logfile_Date/SD_Name

Restored archival path:

5 \$RESTOREDIRE/~~Main~~/Wk_Of_The_Mon/Device_Type/Logfile_Date/SD_Name

A notification indicating that the logfile has been restored is then sent to the DAM via DAM-Event as documented in the CORBA integration document [MA1].

10 Transitioning Restored Logs

Restored logfiles are kept online for the restored logfile duration period, which has a default duration of one month. Restored logfiles are transitioned directly from online to N/A status on a weekly basis in the following manner:

15 As all archival records of a restored log archival table deal with online logs, the first two records used to store the first offline record offset, and the first online record offset are not required to be utilized.

The same process of recreating the associated Directory

20 Reference ID index and archive table as that for non-restored log archival tables is used but with the following difference. For each restored online archival record, the logfile's "last access" timestamp is used to determine if the restored logfile duration has been exceeded.

25

Concurrent Event Handling

The nature of the SM is that it will not have to deal with a large number of transactions-per-second (tps), but rather that the majority of SM transactions will be of a long-lasting nature due to event-caused, prolonged, disk-related activity. Given these system specifics, the SM must be able to handle multiple concurrent events. For example, a

"transfer log to SM" notification from an LCM (SM SR-2), and a "transfer log from SM" notification from the DAM (SM SR-3) can arrive at the same time. Each of these events could potentially result in substantial disk activity given that
 5 logfiles can be of substantial size.

The most efficient means of handling concurrency in this scenario is through lightweight threads. In the worst case of the SM running on a single processor system, the overhead involved in thread creation and in context switching between
 10 threads is minimal when compared to the latency times associated with disk accesses. In the best case, of multiple disk controllers, and multiple processors on a SMP (symmetrical multi-processing) SM system, threads would be able to concurrently process on different processors/disk
 15 controllers. For these reasons, the SM should be implemented using threads rather than by an event loop.

Activity Status File

20 The Activity Status File (ASF) contains state information for various activities going on in the SM. For example, as each logfile transfer notification from the LCM is received, the SM stores the event related information so that if the system crashes, it can restart any pending activity.

25 The information in the stat file can be displayed via SM-GetStatus.

The pending activity file syntax is:

StatFile := SMDIR/" "SM.stt"

The syntax for each record is:

30 ASFEntry := JobNumber Activity
 JobNumber := Integer[4]
 Activity := Archival | Access

```

Archival      :=   Status ";" DateTime ";" SDName ";"
LCMName ";" \
LogRefs
Access       :=   Status ";" DateTime ";" SDType ";" SDName ";"
5  \
SearchAttr ";" LogRefs ";"
Status       :=   "n" // new but not acted on
                | "s" // started job
                | "c" // complete, just cleaning up
10            | "f" // failed, just cleaning up
                | "r" // system failure, job
restarted

```

NOTE: The "r" status applies to the automated analysis mode
 15 since the custom analysis mode is predicated on an initial
 web browser request to the DAM.

Storage Manager Event Logging

The SM logging uses syslog. Syslog should be setup with the
 following parameters:

```

20 void openlog(const char *ident = "SM", int logopt =
LOG_PID+LOG_NOWAIT,
int facility = LOG_USER);

```

A message will be issued when the following occurs:

```

25 SM starts up, including command line parameters
SM shuts down
SM receives SM-GetLogInfo including all parameters
SM receives SM-GetStatus including all parameters
SM receives SM-SetConfigInfo including all parameters
30 SM receives SM-Noop
SM receives NetFile method calls (Open, Get, Put, Close) and
associated parameters

```

Significant state changes during archival jobs (e.g. start, end, misc.)

Significant state changes during the creation/transitioning of archival tables

5 Security related events

When an error occurs

Initially the message part of the syslog() call should be in a machine parsable form. In the future, the message format should follow the Nortel Networks Common Logging Format.

10 For Future Study

A tool to enter and modify SM configuration information.

Archival transitioning per individual security device type archival duration configuration.

Use of a Common Logging Format

15

Appendix A: SM Design Information From SDLRS Design Document

The following is the SM design information from the SDLRS specification design description above.

Storage Manager (SM)

20 The SM is responsible for SD log archival in the correct location, maintaining an index of log archival according to SD and export control configuration settings, and backups of the log archiving system. As part of the log transfer process, the LCM begins a secure log transfer to the SM with

25 the date, device type, and SD name for the log being transferred. From this information, the SM then selects the appropriate on-line archival directory where the log will be written. Upon successful completion of the log transfer, the SM then updates its index of log archival.

30 To manage the transition of logs from on-line to off-line archival, the SM receives from the DAM the log retention configurations for the system on a daily basis. By default

the log archival configurations are set at the following:
perimeter devices - 3 months on-line and 15 months off-line;
export controlled devices - 3 months on-line and 57 months
off-line; drop-box devices - 3 months on-line and 15 months
5 off-line; devices classified as "other" (e.g. SPAM logs) - 3
months on-line. The SM then manages the transition of on-
line log archival to off-line archival by performing disk
cycling, off-line archival backups, and the updating of the
log archival index.

10 Upon receiving log location requests from the DAM, the SM
references the archival index for the location of the log.
If the log is on-line, then the file path is given to the
DAM. If the log is found to be off-line, then the DAM is
informed that the log is off-line. Archival information for
15 specific SD logs or for the complete on-line or off-line
indices can be provided to the DAM on request.
The DAM is responsible for providing the configuration
details to the other system components, ensuring that all SD
logs are archived, performing data analysis on SD logs,
20 providing summary statistics to the Data Analysis Store
(DAS), and querying the SM for log archival information upon
request.

Logs that have been securely pulled, are then securely
pushed to the Storage Manager (SM) for archival with the LCM
25 providing for each log transfer the device type, date, and
SD name to the SM.

As the LCM(s) notify the DAM of the successful transfer of
SD logs, the DAM then contacts the SM for the location of
the SD log such that the appropriate data filter can be
30 applied to the log.

Horne 13806RO

- 94 -

Glossary

- DAM: Data Analysis Manager - the system component which synchronizes the overall system, and performs the analysis on logs.
- 5 DAS: Data Analysis Store - the system database where the system configuration and summary metrics are stored.
- IMMUNESystem: Intrusion Monitoring and Management of Unified NETworks system - an enterprise security environment of which the Security Devices Log and Reporting System is a
- 10 part.
- LC: Log Collector - the system component which directly interfaces with a Security Device logging mechanism.
- LCM: Log Collection Manager - system component which manages the collection of all Security Device logs and
- 15 transfers the logs to the the Log Archival Unit.
- SD: Security Devices - devices used by the enterprise to manage data security within the enterprise network.
- SDLRS: Security Devices Log and Reporting System
- SM: Storage Manager - system component responsible for
- 20 log archival, ad-hoc log retrieval, and backups.
- WAS: Web Application Server - contains the applications which provide the system and data interfaces to the user.
- WS: Web Server - the user's access point into the system
- 25 WC: Web Client - a web browser capable of interfacing with the web server for data presentation to the user.
- SECOPS:
- SECINV:
- SPAM:
- 30 DRID Directory Reference ID

Horne 13806RO

- 95 -

	LRID	Logfile Reference ID
	LEL	Log Exception List
	LTL	Log Transfer List
5	SDF	Security Device File
	LCT	Log Collector Table
	SDT	Security Device Table
	RAS	Remote Access Services

10

Horne 13806R0

- 96 -

WHAT IS CLAIMED IS

1. A security device log and reporting system for a data network, comprising:
 - 5 a Log Collection unit, for collecting log files from security devices,
 - a Data Analysis and Log Archival unit for analysis and archival of log files,
 - and a Data and System Access Unit providing a user interface
 - 10 with the Data Analysis and Log Archival Unit.
2. A system according to claim 1 wherein the Log Collection unit comprises a Log Manager for managing log collection from a plurality of security devices.
- 15 3. A system according to claim 1 wherein the Log Collection unit comprises a plurality of log collectors and a log collection manager for managing log collection from a plurality of log collectors.
- 20 4. A data network security management system for security device log archival and reporting comprising:
 - a log collection units comprising a plurality of log collectors, each for collecting log files from a plurality
 - 25 of security device node and a log manager for collecting log files from a plurality of log collectors;
 - a data analysis and log archival unit for archival and automated analysis of log files received from the log manager.

Horne 13806RO

- 97 -

and a data and system access unit providing a user interface to the Data Analysis and Log Archival Unit.

5. A system according to claim 4 wherein the log collector
5 provides output to a storage manager and a Data Analysis manager, connected to a Data Analysis Store, of the Data Analysis and Log Archival unit, which also comprises a Archival unit associated with the Storage unit.

10 6 A system according to claim 4 wherein the user interface is a web based user interface

7. A system according to claim 1 wherein the data and system
access unit wherein the user interface provides for log
15 analysis summaries, trend analysis, controlled operational access and system configuration

8. A system according to claim 1 wherein the access unit
comprises an authenticated, authorized, secured web based
20 system.

9. A system according to claim 4 wherein the log collector
receives logfiles from security devices comprising one or
more device types including:
25 Firewalls, (raptor 4, Raptor 6, CES CheckPoint Firewall-1)
Remote access services (RAS),
CES (Contivity Extranet Switch),
SPAM (Mail shield),
FTP Drop Box
30 and Anti-Virus (Antigen)

Horne 13806RO

- 98 -

10. A system according to claim 1 wherein the Log Manager LM interfaces with a Data Analysis Manager (DAM) and a Storage Manager (SM) and the LM comprises:

- 5 means for collecting logfiles from security devices,
means for pushing cached SD logfiles to a Storage manager for archival, and
means for providing log archival status updates to a Data Analysis Manager (DAM).

10

11. A Log Manager for a data network security management system, wherein the Log Manager LM interfaces with a Data Analysis Manager (DAM) and a Storage Manager (SM) and the LM comprises:

- 15 means for collecting logfiles from security devices, means for pushing cached SD logfiles to a Storage manager for archival, and means for providing log archival status updates to a Data Analysis Manager (DAM).

- 20 12 A system according to claim 1 wherein the Log Collector Manager (LCM) interfaces with a Data Analysis Manager (DAM) and a Storage Manager (SM) and the LCM comprises:

- means for receiving logfiles from the plurality of log collectors,
25 means for obtaining a logging system configuration from the DAM,
means for propagating the configuration to individual LC associated with Security devices,
means for providing notification to the LC to begin transfer
30 of SD log files, and

Horne 13806R0

- 99 -

means for pushing cached SD log files to the Storage manager
for archival, and
means for providing log archival status updates to the DAM.

- 5 13. A system according to claim 1 wherein the Data Analysis
and Log Archival unit comprises a Storage Manager (SM) and a
Data Analysis Manager (DAM) and the SM comprises
means to receive security device logs from the Log Collector
Manager,
10 means for system archival,
means for management of online and offline log archival and
transition of logs from online to offline status,
means to provide the Data Analysis Manager (DAM) with access
to SD logs on request, and
15 means to provide the DAM with access to the SM log Archival
tables on request.

14. A security device log and reporting system wherein
archival of log files is separated from analysis of
20 logfiles.

15. A security device log and reporting system comprising a
Log Manager, the Log Manager having a distributed interface
for receiving logfiles from a plurality of security devices,
25 and is the interface to a Data Analysis and Archival unit of
the system.

16. A security device log and reporting system according to
claim 15 wherein the Log manager comprises an intermediary

Horne 13806RO

- 100 -

caching system for log files received from the plurality of security devices.

17. A security device log and reporting system according to
5 claim 14 comprising an Data Analysis and Archival Unit, a
Log Collection Unit comprising a Log Manager, and Data and
system Access Unit, wherein Data Analysis and Archival Unit
interfaces with only a Log Manager and a Data and System
Access Unit, whereby interfaces are easily protected via a
10 firewall and intrusion detection system.

18. A method of managing security device log archival and
reporting for a data network security , comprising
collecting log files from a security device node at
15 a log collector
collecting log files from a plurality of log
collectors at a log collection manager
transferring log files from the log collection
manager to a data analysis and log archival unit for
20 archival and analysis.

19. A method of managing security device log archival and
reporting for a data network security , comprising
collecting log files from a security device node at
25 a log collector
collecting log files from a plurality of log
collectors at a log collection manager
transferring log files from the log collection
manager to a data analysis and log archival unit for

Horne 13806RO

- 101 -

archival and analysis, logfile analysis being separated from log file archival.

20 A method according to 18 comprising providing user
5 access to the Data analysis and log archival unit via a a
data and system access unit.

21. A Storage Manager for a security device log archival and
reporting system comprising means for receiving security
10 device logs from the log collector manager for system
archival,
means for management of online and offline log archival
and transition of logs from online to offline status,
means for providing the DAM with access to security device
15 logs on request,
means for providing the DAM with access to the SM log
archival tables on request.


22. A storage manager according to claim comprising means
20 for differentiating types of log files.

Horne 13806RO

- 102 -

ABSTRACT

A system for security management comprising log archival and reporting is provided using a novel architecture with particular application which is scalable for larger scale global data networks. The system comprises a Log Collection unit, interfacing with a Data Analysis and Log Archival unit, and a Data and System Access Unit interfacing with the Data Analysis and Log Archival Unit. The Log Collection Unit comprises a Log Manager for managing log collection from a plurality log collectors interfacing with one or more security devices. The Log Manager may include a log collection manager for managing log collection from a plurality of log collectors. The log collector provides output to a log manager which provides output to a Storage Manager and a Data Analysis manager, connected to a Data Analysis Store, of the Data Analysis and Log Archival unit, which also comprises a Archival unit associated with the Storage unit. The Data and System Access unit provides a user interface, preferably web based.






FIGURE 2.

LOG REPORTING

Login ID:

Password:

ENTER

FIGURE 3

THIS IS THE MAIN MENU

Although all the tabs appear on this example, each individual will only get a subset of these tabs based on the status assigned to their user id.

Initially none of the tabs are selected.

Once a tab has been selected, the menu gets replaced with the content of tabs that have been set up for that particular user.

LOG REPORTING

Metric Results	Configure Filters	Job Status	Logs Archived	Admin
----------------	-------------------	------------	---------------	-------

MAIN MENU

Select tab of choice

FIGURE 4

This is the Main Results Menu

Although all the tabs appear in this example, each individual will only get a subset of these tabs based on the status assigned to their account

Initially none of the tabs are selected

Once a tab has been selected, the menu gets replaced with the menu of tabs that have been set up for that particular

FIGURE 5.

This is the first window that will appear when firewalls are selected from the main menu. The user would also choose this tab if they want to look at another date or firewall.

The user can enter the date and firewall information that they want to look at. They could also choose to review the other firewall elements available by clicking on the different tabs across the top.

Please note that the SEARCH button will only appear if the user is doing the viewing has permission to do a full type search.

Any time the user changes the date, monthly, weekly summary radio buttons, they will be prompted to re-enter a date. If a monthly button is selected, they the date would only be year and month.

FIGURE 6

The data that was selected by the previous window appears on the left in the date or range of dates field.


The results on the right only appear once the submit button has been pressed.

Any changes to the data on the left will cause the results to be recalculated. Another SUBMIT has been done.

The last page could have a total of 10 pages.

If there are more metrics than will appear on the screen, there will be a scrollbar.

This example shows what will be displayed for metrics.



Metric Results - Firewalls

Firewalls

Sum of all Firewalls

Used Statistics

Results Main Menu

List of Firewalls

Date or Range of Dates

- Daily
- Monthly
- Monthly Summary

- Metrics
- Keyword Results

SUBMIT


RESULTS (Row 1 - 5 of 25):

Date	Metric1	Metric2	Metric3
19990101	4567			
19990102	6543			
19990103	9999			
19990104	4567			
19990105	4567			

PAGES OF RESULTS: 1 2 3 4 5

FIGURE 7.

This page shows what will be displayed if the user wants to look at keyword results.



Metric Results - Firewalls

Firewalls

Sum of all Firewalls

Used Statistics

Results Main Menu

List of Firewalls

Date or Range of Dates

- Daily
- Monthly
- Monthly Summary

- Metrics
- Keyword Results

SUBMIT

RESULTS (Row 1 - 2 of 12):

KEYWORD p="csaasg7FOURD:

```

Jan 19 15:56:34 211 opnd171 http(133): 121 Statistics: direction=0.37 id=666 of 4
n=436 code=102 src=V p=3 src=47.12.162.113/1053 src=www-beep44.ca.norad.com
date=7 p=4 date=2004-10-25 20:46:00 domain=www1.synaptica.ca op=GET url=http://www1.synaptica.ca/submit.aspx?pageid=1&result=304U or local copy? p=4 to url=2

```

KEYWORD op(a-s)w.g7FOURD:

```

Jan 19 15:56:34 843 opnd171 http(133): 121 Statistics: direction=0.69 id=666 of 4
n=436 code=102 src=V p=3 src=47.12.162.113/1053 src=www-beep44.ca.norad.com
date=7 p=4 date=2004-10-25 20:46:00 domain=www1.synaptica.ca op=GET url=http://www1.synaptica.ca/submit.aspx?pageid=1&result=304U or local copy? p=4 to url=1

```

PAGES OF RESULTS: 1 2 3 4 5 6

FIGURE 8

The results that was selected by the previous window appears on the left in the month or range of months field.

The results on the right only appears once the submit button has been pressed.

Any change to the info on the left will clear the results and will require a SUBMIT has been done.

The last page could have a total if helpful.

If there are more metrics than will appear on the screen, there will be a scrollbar.

This example shows what will be displayed for metrics.

Metric Results - Firewalls

Firewalls

Sum of all Firewalls

Userid Statistics

Results Main Menu

Monthly Summary of Firewalls

 Month or Range of Months

 • Metrics
 ○ Keyword Results

SUBMIT

RESULTS (Row 1 - 5 of 15):

Month	Metric1	Metric2	Metric3
199901	4567			
199902	6543			
199903	9999			
199904	4567			
199905	4567			

PAGES OF RESULTS: 1 2 3

FIGURE 9

Once the user has selected a date, they must then select a firewall instance. The example on the right shows how the information will be displayed if the user chooses all firewalls and all users.

The results will show a row for each user for each date. The metrics displayed will be a sum for all firewalls.

Metric Results - Firewalls

Firewalls

Sum of all Firewalls

Userid Statistics

Results Main Menu

All Firewalls

 All Users

 Date or Range of Dates

 • Daily
 ○ Monthly
 ◇ Monthly Summary

 • Metrics
 ○ Keyword Results

SUBMIT

RESULTS - SUM FOR ALL FIREWALLS (Row 1 - 5 of 25):

Date	Userid	Metric1	Metric2
19990101	testuser1	4567		
	hdkskls	6543		
	gjkfda	9999		
	sdjfdkls	4567		
19990102	testuser1	4567		

PAGES OF RESULTS: 1 2 3 4 5

FIGURE 10

Once a regular expression has been added, it cannot be changed. Please use the list descriptions and status.com.

When adding a new expression, the status is set to ACTIVE.

Configure Filters - Devices

Device List

Search & Count

Search & SUM

Keywords

Configure Main Menu

List of Device Types

List of Logfile Types

SEARCH FOR A PARTICULAR EXPRESSION AND COUNT THE NUMBER OF LINES WHERE THE TEXT WAS FOUND.

STATUS	REGULAR EXPRESSION	TEXT DESCRIPTION
A/H	telnet.*connection for	Number of Telnet Connections
A/H	ftp.*connection for	Number of FTP Connections
A/H	ftp.*file	Number of FTP File Transfers
A		
A		

Save Changes

FIGURE 11

Job Status - Alarms

Active Severity 1 Alarms

Active Non-Sev 1 Alarms

Acknowledged Alarms

Main Menu

List of Device Types


ALARMXXX - FIREWALL XXXX IS DOWN
more information about the alarm

ACKNOWLEDGE: ☐

ALARMYYY - FIREWALL YYY NOTICED SOMETHING BAD
more information about the alarm

ACKNOWLEDGE: ☐

FIGURE 12



Logs Archived

On Line Logs
Off Line Logs
Main Menu

List of Device Types

Enter a date or a date range (format YYYYMMDD):

Single Date:

OR

Range: to

SUBMIT


FIGURE 13.

To add a new user, the user must have a userid

The entries in the device type list are taken from the device_types table.

The entries for the type of access are taken from the access_type table and are usually DBA, ASHAL, TST.

More than one entry would be made if the user were able to use different device types. If they were able to use DBA for FIREWALLS, an entry would be made and if they were able to use ASHAL, TST for SPAN, a separate entry would be made.



Administration

Users
Owners
Log Collector Manager
Misc Lists
Main Menu

Userid:
User Name: Ext:
Device Type:
Type of Access:

Add the User

FIGURE 14.